

CUDY

AP1200 Outdoor

Kod: 00-00005570 · Access Pointlər



CUDY AP1200 Outdoor AC1200 Wi-Fi Access Point açıq məkanlar üçün xüsusi dizayn edilib. AC1200 sürət, Gigabit Ethernet dəstəyi və hava şəraitinə davamlı korpus sayəsində həyət, anbar, kafe və sənaye sahələrində stabil və geniş simsiz şəbəkə təmin edir. Uzunömürlü və etibarlı həll yoludur.

Texniki göstəricilər



WiFi5

WIFI



Dual band

Genişlik



Mesh

Mesh



2.4Ghz/5Ghz

Tezlik

Ətraflı məlumat

Model	AP1200 Outdoor 1.0
CPU Details	580 MHZ Single-Core CPU
Flash/ROM	8 MB (64 Mbit) NOR
DDR/RAM	64 MB (512 Mbit) DDR2
5 GHz Wi-Fi Speed	867Mbps
2.4 GHz Wi-Fi Speed	300Mbps
5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
Wi-Fi Antennas	2× Detachable
FEM or PA/LNA	• 5 GHz: 2× Internal • 2.4 GHz: 2× Internal
Detachable Wi-Fi Antennas Connector	RP-SMA Female
Beamforming	True
Range Performance	Max: 170 m (558 ft) Park: 150 m (492 ft) Street: 50 m (164 ft) Woods: 30 m (98 ft)
Wall Performance	NA
10/100 Mbps RJ45 Ports	1
Ethernet Notes	Accepts PoE powering
LED	• 5 GHz Wi-Fi • 2.4 GHz Wi-Fi • LAN • Internet • System

Physical Buttons	• WPS Button • Reset Button
Power Interface	PoE via Ethernet Port
Power Methods	Passive PoE
Power Input-an-unordered-list	24V□
Power Adapter in the Box	Input: 100-240V~, 50/60Hz Output: 24V□ Passive PoE
Max Power Consumption (W)	12 W
Idle Power Consumption (W)	2.5 W
EMC	ESD: Contact: 4kV; Air: 8kV IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: -20 °C ~ 60 °C (-4 °F ~140 °F) Extend Operating Temperature with Industrial Grade SIM Card: -40 °C ~ 65 °C (-40 °F ~ 149 °F) Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F) Operating Humidity: 0% ~ 100% non-condensing Storage Humidity: 5% ~ 90% non-condensing
Ingress Protection Rating	IP65 When devices is installed vertically
FCC, CE	
Installation	• Wall-mount • Pole-mount
Dimension	Main Part: 240×100×53.7 mm 9.45×3.94×2.11 inches Antenna: 197.5×21.6×15.5 mm 7.78×0.85×0.61 inches
Product Weight	415 g (14.64 oz.)

• AP1200 Outdoor • Detachable Antennas • PoE Adapter • Power Cord • Mounting Kit • Ethernet Cable • Installation Guide	
Retail Package Weight	EU: 768 g (27.09 oz.)
Retail Package Dimension	324×107×86 mm 12.76×4.21×3.39 inches
Units per Carton	20
Carton Net Weight	EU: 15.4 kg (33.95 lbs)
Carton Gross Weight	EU: 16.3 kg (35.94 lbs)
Carton Dimension	46×33.7×45 cm 18.11×13.27×17.72 inches
Wi-Fi Standards	Wi-Fi 5
Max Wi-Fi Modulation	256-QAM
Wi-Fi Efficiency	MU-MIMO
Wi-Fi Efficiency Note	MU-MIMO available on 5 GHz
Max Capacity	128
Recommended Client Upper Limit	30
Max Wi-Fi Channel Width	80 MHz
Wi-Fi Security	WPA/WPA2/WPA3
WPS	True
Operation Modes	• Wi-Fi Router • Access Point • Range Extender • WISP • Client

WAN Mode	• DHCP • Static IP • PPPOE • PPTP • L2TP
QoS	Per-User Rate Limiting
DHCP	• Address Reservation • DHCP Client List • Server
IP Versions	IPv4/IPv6
IPv6 Protocols	• Relay • Dynamic (SLAAC/DHCPv6) • Static (Fixed IP) • Passthrough • 464XLAT • MAP-E • DS-Lite
IPTV/VLAN	• Bridge • Tag VLAN • VoIP VLAN • IPTV VLAN
TTL Customization	• Extend • Spoof • Custom
IGMP	• IGMP Proxy • IGMP Snooping
Forwarding	• Port Forwarding • Port Triggering • UPnP • DMZ

Firewall	• SPI Firewall • DoS Protection • Block PING
Application Layer Gateway	• IPSec Passthrough • L2TP Passthrough • PPTP Passthrough • FTP Passthrough • TFTP Passthrough • H323 Passthrough • SIP Passthrough • RTSP Passthrough
VPN Client	• OpenVPN • Wireguard • PPTP • L2TP
DNS Options	• Manual DNS • Rebind Protection • Override Clients' DNS
Wake on LAN	True
Online Detection	True
All Devices Management	• Wi-Fi Time Schedule • MAC Filter • IP/MAC Binding
Per-Devices Management	• Internet On/Off • VPN On/Off • Online Time Schedule • Device Rename
Content Management	• Domain Filter • IP Filter
Local Control Method	• Config Web Page • App Control

Remote Control Method	• TR069/TR098/TR111/TR143/TR181 • Config Page via HTTP
Firmware Upgrade	Local Update
Reliability	• Timed Reboot • Backup and Restore
Diagnostic Tools	• Diagnosis • Ping • Traceroute • NSLookup • System Log
Languages	• English • German • Spanish • French • Hebrew • Italian • Portuguese • Ukrainian • Russian • Korean
Panel	• Internet Status • Devices Management • WAN Status • LAN Status • WISP Status • Wi-Fi Status • VPN Status • DHCP Server Status • System Version
Charts	• Internet Speed • WISP Speed • Wi-Fi Speed

Internet Failover Sequence

- WAN
- WISP

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az