CUDY

AP3000 AX3000 High Power WiFi 6 Outdoor Access Point

Kod: 00-00006245 · Access Pointlər



Cudy AP3000 Outdoor, açıq havada yüksək sürətli internet təmin edən AX3000 Wi-Fi 6 Access Point-dir. IP65 hava şəraitinə dözümlü korpusu, High Power gücləndiriciləri və PoE dəstəyi ilə həyət, park və obyektlər üçün mükəmməl kənar şəbəkə həllidir.

Texniki göstəricilər

WiFi6 WIFI	**Dual band** Genişlik
Mesh Mesh	**2.4Ghz/5Ghz** Tezlik
PoE PoE	**100+** Qoşulma sayı

Ətraflı məlumat

AP3000 Outdoor 1.0	
CPU Details	1.3 GHz Dual-Core CPU
Flash/ROM	128 MB (1 Gbit) NAND
DDR/RAM	256 MB (2 Gbit) DDR3
5 GHz Wi-Fi Speed	2402Mbps
2.4 GHz Wi-Fi Speed	574Mbps
5 GHz Wi-Fi Streams	2 Spatial Streams with 3T3R
2.4 GHz Wi-Fi Streams	2 Spatial Streams
Wi-Fi Antennas	1× Internal+2× External
FEM or PA/LNA	5 GHz: 3× High-Power, 2.4 GHz: 2× High-Power
Detachable Wi-Fi Antennas Connector	RP-SMA Female
Beamforming	
Range Performance	Max: 320 m (1050 ft) Park: 280 m (919 ft) Street: 70 m (230 ft) Woods: 40 m (131 ft)
Gigabit RJ45 Ports	1
Ethernet Notes	ETH0: PoE In
LED	System
Physical Buttons	WPS Button, Reset Button
Power Input Type	PoE via Ethernet Port
Power Methods	• 802.3at PoE • Passive PoE
Power Input	• PoE: 802.3at • Passive PoE: 48-57V□

Max Power Consumption (W)	19W
Idle Power Consumption (W)	5 W
Power Adapter In the Box	Input: 100-240V~, 50/60Hz Output: 48V Passive PoE
Advanced	Hardware Watchdog
EMC	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: -40 ℃ ~ 65 ℃ (-40 ℉ ~149 ℉) Extend Operating Temperature with Industrial Grade SIM Card: -40 ℃ ~ 70 ℃ (-40 ℉ ~ 158 ℉) Storage Temperature: -40 ℃ ~ 70 ℃ (-40 ℉ ~ 158 ℉) Operating Humidity: 0% ~ 100% non-condensing Storage Humidity: 10% ~ 95% non-condensing
Ingress Protection Rating	IP65 When devices is installed vertically
FCC, CE	
Installation	• Wall-mount • Pole-mount
Dimension	Main Part: 240×100×53.7 mm 9.45×3.94×2.11 inches Antenna: 197.5×21.6×15.5 mm 7.78×0.85×0.61 inches
Product Weight	455 g (16.05 oz.)
• AP3000 Outdoor • Detachable Antennas • PoE Adapter • Power Cord • Mounting Kit • Ethernet Cable • Installation Guide	
Retail Package Weight	EU: 856 g (30.19 oz.)

Retail Package Dimension	324×107×86 mm 12.76×4.21×3.39 inches
Units per Carton	20
Carton Net Weight	EU: 20.6 kg (45.42 lbs)
Carton Gross Weight	EU: 21.4 kg (47.18 lbs)
Carton Dimension	46×33.7×45 cm 18.11×13.27×17.72 inches
Compatible Products	C200P 1.0, C500P 1.0
Compatible Accessories	POE200 2.0, POE300 2.0, POE400 2.0, POE350 2.0, POE200H 1.0, POE400X 2.0, POE350 3.0, POE400 3.0, POE300 3.0, POE52-30W 1.0, POE48-18W 1.0

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az