

AP3000 OUTDOOR

CUDY AP3000 AX3000 High Power Outdoor Access Point açıq məkanlar üçün ideal Wi-Fi 6 həllidir. Güclü signal ötürməsi, geniş əhatə dairəsi və Gigabit Ethernet dəstəyi sayəsində həyət, obyekt, anbar və sənaye sahələrində sürətli və stabil simsiz internet bağlantısı yaradır.



Specifications

Model	AP3000 Outdoor
Brand	Cudy
WIFI	WiFi6
Geni?lik	Dual band
Mesh	Mesh
Tezlik	2.4Ghz/5Ghz
PoE	PoE
Qo?ulma say?	300+

KEY FEATURES

Model	AP3000 Outdoor 1.0
CPU Details	1.3 GHz Dual-Core CPU
Flash/ROM	128 MB (1 Gbit) NAND
DDR/RAM	256 MB (2 Gbit) DDR3
5 GHz Wi-Fi Speed	2402Mbps
2.4 GHz Wi-Fi Speed	574Mbps
5 GHz Wi-Fi Streams	3T3R (3×3 MIMO)
2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
Wi-Fi Antennas	1× Internal+2× External
FEM or PA/LNA	• 5 GHz: 3× High-Power • 2.4 GHz: 2× High-Power
Detachable Wi-Fi Antennas Connector	RP-SMA Female
Beamforming	True
Range Performance	Max: 320 m (1050 ft)
	Park: 280 m (919 ft)
	Street: 70 m (230 ft)
	Woods: 40 m (131 ft)
Wall Performance	NA
Gigabit RJ45 Ports	1
Ethernet Notes	Accepts PoE powering
LED	System
Physical Buttons	• WPS Button
	• Reset Button
Power Interface	PoE via Ethernet Port
Power Methods	• 802.3at PoE
	• Passive PoE
Power Input-an-unordered-list	PoE: 802.3at, Passive PoE: 48-57V
Power Adapter in the Box	Input: 100-240V~, 50/60Hz Output: 48V Passive PoE
Max Power Consumption (W)	18 W
Idle Power Consumption (W)	5 W
Advanced	Hardware Watchdog
EMC	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV
	IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: -40 ~ 65 (-40 ~ 149)
	Extend Operating Temperature with Industrial Grade SIM Card: -40 ~ 70 (-40 ~ 158)
	Storage Temperature: -40 ~ 70 (-40 ~ 158)
	Operating Humidity: 0% ~ 100% non-condensing Storage Humidity: 10% ~ 95% non-condensing

Ingress Protection Rating	IP65 When devices is installed vertically
FCC, CE	
Installation	• Wall-mount • Pole-mount
Dimension	Main Part: 240×100×53.7 mm 9.45×3.94×2.11 inches Antenna: 197.5×21.6×15.5 mm 7.78×0.85×0.61 inches
Product Weight	455 g (16.05 oz.)
• AP3000 Outdoor • Detachable Antennas • PoE Adapter • Power Cord • Mounting Kit • Ethernet Cable • Installation Guide	
Retail Package Weight	EU: 856 g (30.19 oz.)
Retail Package Dimension	324×107×86 mm 12.76×4.21×3.39 inches
Units per Carton	20
Carton Net Weight	EU: 20.6 kg (45.42 lbs)
Carton Gross Weight	EU: 21.4 kg (47.18 lbs)
Carton Dimension	46×33.7×45 cm 18.11×13.27×17.72 inches