CUDY

AP3000S AX3000 WI-FI 6 Gigabit Access Point

Kod: 00-00006242 · Access Pointlər



Cudy AP3000S, tavan tipli AX3000 Wi-Fi 6 Gigabit Access Point-dir. Yüksək sürət, OFDMA və MU-MIMO texnologiyaları ilə çoxsaylı cihaz qoşulduqda stabil internet təmin edir. PoE dəstəyi və estetik dizaynı ilə ofis, otel və ticarət obyektləri üçün mükəmməl şəbəkə həllidir.

Texniki göstəricilər

WiFi6 WIFI	**Dual band** Genişlik
Mesh Mesh	**2.4Ghz/5Ghz** Tezlik
PoE PoE	

Ətraflı məlumat

AP3000S 1.0	
CPU Details	1.2 GHz Dual-Core CPU
Flash/ROM	128 MB (1 Gbit) NAND
DDR/RAM	128 MB (1 Gbit) DDR3
5 GHz Wi-Fi Speed	2402 Mbps
2.4 GHz Wi-Fi Speed	574 Mbps
5 GHz Wi-Fi Streams	2 Spatial Streams
2.4 GHz Wi-Fi Streams	2 Spatial Streams
Wi-Fi Antennas	4× Internal
FEM or PA/LNA	5 GHz: 2× Internal, 2.4 GHz: 2× Internal
Beamforming	
Range Performance	Max: 200 m (656 ft) Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
Wall Performance	Two wooden walls with thickness < 10 cm (4'') One concrete wall with thickness < 20 cm (7'') or two concrete walls with thickness < 10 cm (4'')
Gigabit RJ45 Ports	1
Ethernet Notes	ETH0: PoE In
LED	System
Physical Buttons	Reset Button
Power Input Type	• DC Jack • PoE via Ethernet Port

Power Methods	• DC • Passive PoE • 802.3at/af PoE
Power Input	• DC: 12V 1A • Passive PoE: 48V • PoE: 802.3at/af
Max Power Consumption (W)	12W (PoE), 8.8W (DC)
Idle Power Consumption (W)	2.5W
EMC	ESD: Contact: 4kV; Air: 8kV
Environment	Operating Temperature: -10 ℃ ~ 65 ℃ (14 ℉ ~149 ℉) Storage Temperature: -40 ℃ ~ 70 ℃ (-40 ℉ ~ 158 ℉) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
FCC, CE	
Installation	• Wall-mount • Ceiling-mount
Dimension	Φ171.4×41 mm Φ6.75×1.61 inches
Product Weight	223.3 g (7.88 oz.)
• AP3000S • Mounting Kit • Installation Guide	
Retail Package Weight	EU: 328.1 g (11.57 oz.)
Retail Package Dimension	Adapter Not Included |: 172×172×49 mm 6.77×6.77×1.93 inches
Units per Carton	Adapter Not Included |: 30
Carton Net Weight	EU: 9.8 kg (21.61 lbs)

Carton Gross Weight	EU: 10.6 kg (23.37 lbs)
Carton Dimension	Adapter Not Included |: 54.2×27.4×36.5 cm 21.34×10.79×14.37 inches
Compatible Products	C200P 1.0, C500P 1.0
Compatible Accessories	POE200 2.0, POE300 2.0, POE400 2.0, POE350 2.0, POE200H 1.0, POE400X 2.0, POE350 3.0, POE400 3.0, POE300 3.0, POE52-30W 1.0, POE48-18W 1.0

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az