CUDY

AP3600_P BE3600 WI-FI 6 Gigabit Access Point

Kod: 00-00006243 · Access Pointlər



Cudy AP3600_P, modern BE3600 Wi-Fi 7 Gigabit Access Point-dir. Yüksək ötürmə sürəti, ultra-aşağı gecikmə və geniş əhatə dairəsi ilə çoxsaylı cihaz qoşulduqda stabil internet təmin edir. PoE+ dəstəyi və estetik dizaynı ilə ofis, otel və ticarət obyektləri üçün mükəmməl seçimdir.

Texniki göstəricilər

WiFi7 WIFI	**Dual band** Genişlik
Mesh Mesh	**2.4Ghz/5Ghz** Tezlik
PoE PoE	

Ətraflı məlumat

AP3600 1.0	
CPU Details	2.0 GHz Quad-Core, ARM Cortex-A7
Flash/ROM	128 MB (1 Gbit) NAND
DDR/RAM	512 MB (4 Gbit) DDR3L
MLO Speeds	3570 Mbps
5 GHz Wi-Fi Speed	2882 Mbps
2.4 GHz Wi-Fi Speed	688 Mbps
5 GHz Wi-Fi Streams	2 Spatial Streams
2.4 GHz Wi-Fi Streams	2 Spatial Streams
Wi-Fi Antennas	4× Internal
FEM or PA/LNA	5 GHz: 2× Internal, 2.4 GHz: 2× Internal
Beamforming	
Range Performance	Max: 220 m (722 ft) Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
Wall Performance	Two wooden walls with thickness < 10 cm (4'') One concrete wall with thickness < 20 cm (7'') or two concrete walls with thickness < 10 cm (4'')
2.5G RJ45 Ports	1
Gigabit RJ45 Ports	1
Ethernet Notes	ETH0: PoE In
LED	System
Physical Buttons	Reset Button
Power Input Type	• DC Jack • PoE via Ethernet Port

Power Methods	• DC • Passive PoE • 802.3at/af PoE
Power Input	• DC: 12V⎓ 1A • Passive PoE: 48-57V⎓ • PoE: 802.3at/af
Max Power Consumption (W)	10W
Power Adapter In the Box	AP3600 | No adapter in the box AP3600_P | PoE adapter in the box: Input: 100-240V~, 50/60Hz Output: 48V⎓ Passive PoE
Advanced	Hardware Watchdog
EMC	ESD: Contact: 4kV; Air: 8kV
Environment	• Operating Temperature: 0 ℃ ~ 40 ℃ (32 ℉ ~104 ℉) • Storage Temperature: -40 ℃ ~ 70 ℃ (-40 ℉ ~ 158 ℉) • Humidity: 10% ~ 90% non-condensing • Storage Humidity: 5% ~ 95% non-condensing
FCC, CE	
Installation	• Wall-mount • Ceiling-mount
Dimension	231.9×231.9×57.1 mm 9.13×9.13×2.25 inches
Product Weight	• Adapter Not Included | EU: 435.0 g (15.34 oz.) • EU: 435.0 g (15.34 oz.) • With PoE Adapter (_P) | EU: 435.0 g (15.34 oz.)
• AP3600 • Mounting Kit • Installation Guide • PoE Adapter (_P Model Only) • Ethernet Cable (_P Model Only)	

Retail Package Weight	• EU: 843.0 g (29.74 oz.) • With PoE Adapter (_P) | EU: 843.0 g (29.74 oz.)
Retail Package Dimension	310×238×73 mm 12.2×9.37×2.87 inches
Units per Carton	10
Carton Net Weight	• EU: 8.5 kg (18.74 lbs) • With PoE Adapter (_P) | EU: 8.5 kg (18.74 lbs)
Carton Gross Weight	• EU: 9.4 kg (20.72 lbs) • With PoE Adapter (_P) | EU: 9.4 kg (20.72 lbs)
Carton Dimension	49.5×38.7×33.2 cm 19.49×15.24×13.07 inches
Compatible Products	C200P 1.0, C500P 1.0
Compatible Accessories	POE200H 1.0, POE52-30W 1.0, POE48-18W 1.0
Note	Choose with caution: some suggested models may not deliver speeds that match the device’s maximum capability.

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az