ARCHER C20

Tp Link router Archer C20 AC750 5 GHz diapazonunda 433 Mbps və 2,4 GHz diapazonunda 300 Mbps

Specifications

Model	Archer C20
Brand	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Geni?lik	Dual band
Port sür?ti	100 mb/s

KEY FEATURES

WIRELESS

Standards	Wi-Fi 5 IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	AC750 5 GHz: 433 Mbps (802.11ac) 2.4 GHz: 300 Mbps (802.11n)
WiFi Range	2 Bedroom Houses3× Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas
WiFi Capacity	MediumDual-Band Allocate devices to different bands for optimal performance
Working Modes	Router Mode Access Point Mode Range Extender Mode

HARDWARE

Processor	Single-Core CPU
Ethernet Ports	1× 10/100 Mbps WAN Port 4× 10/100 Mbps LAN Ports
Buttons	WPS/Wi-Fi Button Power On/Off Button Reset Button
Power	9 V ⎓ 0.6 A

SECURITY

WiFi Encryption	WEP WPA WPA2 WPA/WPA2-Enterprise (802.1x) WPA3-Personal
Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network

SOFTWARE

Protocols	IPv4 IPv6
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP

SOFTWARE

Quality of Service	QoS by Device
NAT Forwarding	Virtual Server
	Port Forwarding
	Port Triggering
	DMZ
	UPnP
IPTV	IGMP Proxy
	IGMP Snooping
DHCP	Address Reservation
	DHCP Client List
	Server
DDNS	NO-IP
	Comex
	DynDNS
Management	Tether App
	Webpage

OTHER

System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
	Cable or DSL Modem (if needed)
	Subscription with an internet service provider (for internet access)
Certifications	FCC, CE, RoHS
Environment	Operating Temperature: 0℃~40℃ (32℉ ~104℉)
	Storage Temperature: -40℃~70℃ (-40℉ ~158℉)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

TEST DATA

WiFi Transmission Power	CE:
	<20dBm(2.4GHz)
	<23dBm(5GHz)
WiFi Reception Sensitivity	5GHz:
	11a 54M: -76dBm; 11ac VHT20 MCS8: -71dBm;
	11ac VHT40 MCS9: -66dBm; 11ac VHT80 MCS9:
	-62dBm
	2.4GHz:
	11g 54M: -76dBm11n; HT20 MCS7: -73dBm;
	11n HT40 MCS7: -71dBm

PHYSICAL

Dimensions (W×D×H)	9.1 × 5.7 × 1.4 in
	(230 × 144 × 35 mm)
Package Contents	Wi-Fi Router Archer C20
	Power Adapter
	RJ45 Ethernet Cable
	Quick Installation Guide