

ARCHER C64

Tp Link C64 AC1200 MU-MIMO EasyMesh 5 GHz diapazonunda 867 Mbps və 2,4 GHz diapazonunda 400 Mbps



Specifications

Model	Archer C64
Brand	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Mesh	Mesh
Geniqlik	Dual band
Port sür?ti	1000 mb/s

KEY FEATURES

WIRELESS

	Wi-Fi 5
Standards	IEEE 802.11ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	AC1200 5 GHz: 867 Mbps (802.11ac) 2.4 GHz: 400 Mbps (802.11n)
WiFi Range	3 Bedroom Houses 4× Fixed High-Performance Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas
	Beamforming Concentrates wireless signal strength towards clients to expand WiFi range
	MediumDual-Band Allocate devices to different bands for optimal performance
WiFi Capacity	MU-MIMO Simultaneously communicates with multiple MU-MIMO clients
	Airtime Fairness Improves network efficiency by limiting excessive occupation
Working Modes	Router Mode Access Point Mode

HARDWARE

Ethernet Ports	1× Gigabit WAN Port 4× Gigabit LAN Ports
Buttons	WPS/Reset Button
Power	12V = 1A

SECURITY

WiFi Encryption	WPA WPA2 WPA3 WPA/WPA2-Enterprise (802.1x)
Network Security	SPI Firewall Access Control IP and MAC Binding
Guest Network	1× 2.4 GHz Guest Network 1× 5 GHz Guest Network

SOFTWARE

Protocols	IPv4 IPv6
EasyMesh	Mesh networking creates smooth, fast, stable roaming. Archer C64 can flexibly build an EasyMesh network with EasyMesh-Compatible devices, which eliminates Wi-Fi dead zones, expand your network, and fill your entire home with high-speed Wi-Fi. Seamless Wi-Fi connections with one network name, one-click setting and flexible scalability.
Parental Controls	URL Filtering Time Controls

SOFTWARE

	Dynamic IP
	Static IP
WAN Types	PPPoE(Dual Access)
	PPTP(Dual Access)
	L2TP(Dual Access)
Quality of Service	QoS by Device
	OTA Firmware Upgrade
Cloud Service	TP-Link ID
	DDNS
	Port Forwarding
NAT	Port Triggering
Forwarding	UPnP
	DMZ
	IGMP Proxy
IPTV	IGMP Snooping
	Bridge
	Tag VLAN
	Server
DHCP	DHCP Client List
	Address Reservation
	TP-Link
DDNS	NO-IP
	DynDNS
Management	Tether App
	Webpage

OTHER

Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser

System Requirements	Cable or DSL Modem (if needed)
	Subscription with an internet service provider (for internet access)
Certifications	CE, RoHS
	Operating Temperature: 0~40 (32 ~104)
Environment	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

TEST DATA

	CE:
WiFi Transmission Power	<20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz)
	FCC:
	<30dBm(2.4 GHz & 5 GHz)
	5 GHz:
	11a 6Mbps:-95dBm
	11a 54Mbps:-77dBm
	11ac VHT20 MCS8:-71dBm
	11ac VHT40 MCS9:-67dBm
	11ac VHT80 MCS9:-63dBm
WiFi Reception Sensitivity	2.4 GHz:
	11g 6Mbps: -96dBm
	11g 54Mbps: -78dBm
	11n HT20 MCS7:-77dBm
	11n HT40 MCS7:-74dBm