

# Archer VR400

Tp-link modem router Archer VR400 MU-MIMO, OneMesh, 867 Mbps (5 GHz) + 300 Mbps (2.4 GHz) ikili diapazonlu WiFi, VDSL2/ADSL2+/ADSL2/ADSL standartları, həmçinin fiber, kabel və 3G/4G internet xidmətləri ilə tam uyğundur.

Model	Archer VR400
Brend	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Mesh	Mesh
Genişlik	Dual band
Port sürəti	1000 mb/s



## Specification

HARDWARE FEATURES	
Interface	3× 10/100/1000Mbps RJ45 LAN Ports, 1× 10/100/1000Mbps RJ45 WAN/LAN Port, 1× RJ11 Port, 1× USB 2.0 Port
Button	WPS Button, Wi-Fi On/Off Button, Reset Button
External Power Supply	12V/1A
IEEE Standards	IEEE 802.3, IEEE 802.3u, 802.3ab
VDSL2 Standards	ITU G.993.2, Up to 17a profile (POTS) ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)
ADSL Standards	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs),
ADSL2 Standards	ITU-T G.992.3 (G.DMT.bis)
ADSL2+ Standards	ITU-T G.992.5
Dimensions ( W x D x H )	8.5 × 4.9 × 1.2 in (215.6 × 124.6 × 31.6 mm)
Antenna Type	2× fixed Omini-Directional antennas

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
Frequency	2.4 GHz and 5 GHz
Signal Rate	867Mbps at 5 GHz, 300Mbps at 2.4 GHz
Wireless Functions	Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Transmission Power	<20dBm (2.4 GHz), <23dBm (5 GHz)

WIRELESS FEATURES	
Wireless Schedule	Support 2.4 GHz and 5 GHz Wireless Schedule

SOFTWARE FEATURES	
Security	NAT Firewall, SPI Firewall, Access Control, Service Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding
Operating Modes	VDSL/ADSL Modem Router, Wireless Router, 3G/4G Router
Management	Web-Based Configuration (HTTP / HTTPS), Remote management, SSL for TR-069, SNMP v1/2c, Firmware Upgrade, Diagnostic Tools, Free Online Firmware Update
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port Forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Dynamic DNS	DynDns, NO-IP, TP-Link
VPN	OpenVPN, PPTP VPN, IPsec VPN
Protocols	Supports IPv4 and IPv6
ATM/PPP Protocols	ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER/IPvE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
Advanced Features	Parental Controls, Network Address Translation(NAT), Port Mapping (Grouping), Static Routing, DDNS, IGMP V1/V2/V3
Guest Network	2.4GHz Guest Network, 5GHz Guest Network

OTHERS	
Certification	CE, RCM, RoHS
Package Contents	AC1200 Wireless MU-MIMO VDSL/ADSL Modem Router Archer VR400 External Splitter RJ11 DSL Cable RJ45 Ethernet Cable Power Adapter Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, macOS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Subscription with an internet service provider (for internet access)
Environment	Operating Temperature: 0~40 (32~104) Operating Humidity: 10%~90% non-condensing