

# ARCHER VR600

Tp-link modem router Archer VR600 MU-MIMO, OneMesh, 1733 Mbps (5 GHz) + 300 Mbps (2.4 GHz) ikili diapazonlu WiFi, VDSL2/ADSL2+/ADSL2/ADSL standartları, həmçinin fiber, kabel və 3G/4G internet xidmətləri ilə tam uyğundur.



## Specifications

Model	Archer VR600
Brand	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Mesh	Mesh
Geniqlik	Dual band
Port sürəti	1000 mb/s

KEY FEATURES

HARDWARE FEATURES

<b>Ports</b>	<b>3 Gigabit LAN Ports, 1 Gigabit LAN/WAN Port, 1 RJ11 Port, 1 USB Port</b>
<b>Button</b>	<b>WPS Button, Reset Button, Power On/Off Button, Wi-Fi Button, LED On/Off Button</b>
<b>External Power Supply</b>	<b>12V/1.5A</b>
<b>IEEE Standards</b>	<b>IEEE 802.3, IEEE 802.3u, 802.3ab</b>
<b>VDSL2 Standards</b>	<b>ITU G.993.2, Up to 35b profile (POTS) ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)</b>
<b>ADSL Standards</b>	<b>Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs)</b>
<b>ADSL2 Standards</b>	<b>ITU-T G.992.3 (G.DMT.bis),</b>
<b>ADSL2+ Standards</b>	<b>ITU-T G.992.5</b>
<b>Dimensions ( W x D x H )</b>	<b>8.5 × 6.5 × 1.4 in (216 × 164 × 36.8 mm)</b>
<b>Antenna Type</b>	<b>3 External Dual Band Antennas + 1 Internal 5 GHz Antenna</b>

WIRELESS FEATURES

<b>Wireless Standards</b>	<b>IEEE 802.11ac/n/a 5 GHz, IEEE 802.11b/g/n 2.4 GHz</b>
<b>Frequency</b>	<b>2.4 GHz and 5 GHz</b>
<b>Signal Rate</b>	<b>1733 Mbps on 5 GHz, 300 Mbps on 2.4 GHz</b>
<b>Transmit Power</b>	<b>&lt;20dBm (2.4 GHz), &lt;23dBm (5 GHz)</b>
<b>Wireless Functions</b>	<b>Enable/Disable Wireless Radio, Wireless Statistics</b>
<b>Wireless Security</b>	<b>64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions</b>
<b>Wireless Schedule</b>	<b>Support 2.4 GHz and 5 GHz Wireless Schedule</b>

SOFTWARE FEATURES

<b>Security</b>	<b>NAT Firewall, SPI Firewall, Access Control, Service Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding</b>
<b>Operating Modes</b>	<b>VDSL/ADSL Modem Router, 3G/4G Router, Wireless Router</b>
<b>Management</b>	<b>Web-Based Configuration (HTTP / HTTPS ), Remote management, Command Line Interface, SSL for TR-069, SNMP v1/2c, Firmware Upgrade, Diagnostic Tools, Free Online Firmware Update</b>
<b>DHCP</b>	<b>Server, Client, DHCP Client List, Address Reservation, DHCP Relay</b>
<b>Port Forwarding</b>	<b>Virtual Server, Port Triggering, DMZ, ALG, UPnP</b>
<b>Dynamic DNS</b>	<b>DynDns, NO-IP, TP-Link</b>
<b>VPN</b>	<b>OpenVPN, PPTP VPN, IPSec VPN</b>
<b>Protocols</b>	<b>Supports IPv4 and IPv6</b>
<b>ATM/PPP Protocols</b>	<b>ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER/IPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs</b>
<b>Advanced Features</b>	<b>Parental Controls, Network Address Translation (NAT), Static Routing, DNS Relay, DDNS, IGMP V1/V2/V3</b>

**SOFTWARE FEATURES**

**Guest Network** 2.4 GHz Guest Network, 5 GHz Guest Network  
**IPSec VPN** Supports up to 10 IPSec VPN tunnels

**OTHERS**

<b>Certification</b>	<b>CE, RCM, RoHS</b>
<b>Package Contents</b>	<b>DSL Modem Router External Splitter RJ11 DSL Cable RJ45 Ethernet Cable Power Adapter Quick Installation Guide</b>
<b>System Requirements</b>	<b>Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, Mac OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Subscription with an internet service provider (for internet access)</b>
<b>Environment</b>	<b>Operating Temperature: 0~40 (32 ~104) Operating Humidity: 10%~90% non-condensing</b>