

Archer VR900

Tp-link modem router Archer VR400 MU-MIMO, OneMesh, 1300 Mbps (5 GHz) + 600 Mbps (2.4 GHz) ikili diapazonlu WiFi, VDSL2/ADSL2+/ADSL2/ADSL standartları, həmçinin fiber, kabel və 3G/4G internet xidmətləri ilə tam uyğundur.



Model	Archer VR900
Brend	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Mesh	Mesh
Genişlik	Dual band
Port sürəti	1000 mb/s

Specification

HARDWARE FEATURES	
Interface	1 10/100/1000Mbps RJ45 WAN/LAN Port 3 10/100/1000Mbps RJ45 LAN Ports 1 RJ11 Port 2 USB 3.0 Port
Button	WPS Button, Reset Button, LED On/Off Button, Wireless On/Off Button, Power On/Off Button
External Power Supply	12V/2.5A
IEEE Standards	IEEE 802.3, IEEE 802.3u, 802.3ab
VDSL2 Standards	ITU-T G.993.2, Up to 17a profile (POTS) ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)
ADSL Standards	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1
ADSL2 Standards	ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)
ADSL2+ Standards	ITU-T G.992.5
Dimensions (W x D x H)	216 x 164 x 36.8mm
Antenna Type	3 external detachable dual band antennas (RP-SMA)
Antenna Gain	3 x 2dBi for 2.4GHz and 3 x 3dBi for 5GHz

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz
Wireless Speeds	1300Mbps at 5GHz, 600Mbps at 2.4GHz
Frequency	2.4GHz and 5GHz
Transmit Power	<20dBm(EIRP)
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics Support 2.4GHz and 5GHz Wireless Schedule
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions, Wireless MAC Filtering

SOFTWARE FEATURES	
Quality of Service	ATM QoS, Traffic Control (IP QoS)
Security	NAT Firewall, Access Control, MAC / IP / URL Filtering, IP and MAC Address Binding
Operating Modes	VDSL/ADSL Modem Router, Wireless Router, 3G/4G Router
Management	Web Based Configuration (HTTP), Remote management, SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools, Free Online Firmware Update
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port Forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPsec Passthrough
Protocols	Supports IPv4 and IPv6
ATM/PPP Protocols	ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER/VPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
Advanced Functions	Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, RIP v1/v2(optional), DNS Relay, DDNS, IGMP V1/V2/V3
USB Sharing	Support Samba(Storage)/FTP Server/Media Server/Printer Server, 3G/4G Modem
Guest Network	2.4GHz guest network x 1, 5GHz guest network x 1
IPsec VPN	Supports up to 10 IPsec VPN tunnels

OTHERS	
Certification	CE, RCM, RoHS
Package Contents	AC1900 Wireless Dual Band Gigabit VDSL/ADSL Modem Router Archer VR900 External Splitter RJ11 DSL Cable RJ45 Ethernet Cable Power Adapter Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Cable or DSL Modem Subscription with an Internet Service Provider (for Internet access)
Environment	Operating Temperature: 0~40 (32~104) Storage Temperature: -40~70 (-40~158) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing