

ASI1201A-D

Dahua ASI1201A-D – RFID standalone giriş nəzarət cihazıdır. Kart və şifrə ilə idarə olunan bu model, sadə quraşdırma və istifadəsi ilə seçilir. Kiçik ofislər, biznes mərkəzləri və müəssisələrdə təhlükəsiz giriş nəzarətini təmin edir.



Specifications

Model	ASI1201A-D
Brand	Dahua
Cihaz tipi	Reader
Kart tipi	ID
Qoʻulma	Lan

KEY FEATURES

System	
Main Processor	32 Bit
Memory	16M
Input/Output Ports	
Input	Door sensor x 1, Exit button x 1, Alarm input x 1
Output	Relay :Door lock × 1
	TTL: Bell× 1, Alarm×2
Reader	
Card Read	Reader x 1
Read Format	13.56MHz(Mifare)/125KHz(“-D” EM, Optional)
Read Range	3-8cm (max.)
Response Time	<0.1s
Capacity	
Cardholders	30,000
Events	150,000
Function	
User Management	General, VIP, Guest, Patrol, Block list, Duress
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm
Period Setting	Support 128 groups of schedule, 128 groups of periods and 128 groups of holiday periods
Interface	
To PC	RJ45(10/100M)
To Reader	Wiegand/ RS485
Genreal	
RTC	Yes
Voice Prompt	No
Beep Tone	Buzzer
Keyboard	Sensitive touch keypad with blue backlight
Power Supply	9-15DC/200mA
Working Environment	-5°C~+55°C
Working Humidity	≤95%
Dimension(W×D×H)	97mm*16mm *150mm
Weight	0.3Kg