DAHUA

ASI1201E

Kod: 00-00001112 · Access Control



Dahua ASI1201E suya davamlı RFID standalone giriş nəzarət cihazıdır. İstifadəçilərin kart və şifrə ilə girişini dəstəkləyir, daxili və açıq havada quraşdırıla bilər. Sadə, etibarlı və davamlı quruluşu ilə ofis, bina və müəssisələr üçün ideal seçimdir.

Texniki göstəricilər

Reader	Cihaz tipi
IC	Kart tipi
Lan	Qoşulma
IP66	Qoruma

Ətraflı məlumat

Technical Specification		
Mode	ASI1201E	ASI1201E-D
System		
Main Processor	32 Bit	
Input/Output Ports		
Input	Door sensor x 1, Exit button x 1	
Output	Relay x 1 (Door lock,)	
Reader	Reader x 1	
Card Read		
Read Format	13.56MHz	125KHz
Read Range	1cm–2cm (max.)	
Response Time	<0.1s	
Capacity		
Cardholders	30,000	
Events	60,000	
Function		
User Management	General, VIP, Guest, Patrol, Block list, Duress	
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm	
Period Setting	Support 128 groups of schedule, 128 groups of periods and 128 groups of holiday periods	
Interface		
To PC	RJ45(10/100M)	
To Reader	Wiegand26/34, RS485	
Genreal		
Ingress Protection	IP66 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)	

RTC	Yes
Beep Tone	Buzzer
Keyboard	Sensitive touch keypad with blue backlight
Power Supply	DC 9-15V/100mA
Operating Temperature	-30°C to +55°C
Working Humidity	10%RH–90%RH (no-condensation)
Dimension(W×D×H)	62.0mm×142.0mm×23.0mm
Weight	0.5kg
Working Environment	Outdoor
Certificates	
CE	Yes
FCC	Yes

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az