eurotech
Taste of technology

TEXNIKI SƏNƏD

09.11.2026

TP-LINK

AX10

Kod: 00-00002959 · Routerlər



TP-Link Archer AX10 — AX1500 sürətli Wi-Fi 6 routerdir. 4 nüvəli güclü prosessor, OFDMA və MU-MIMO texnologiyası ilə daha stabil və sürətli internet təqdim edir. Ev və ofislərdə oyun, video axın və çoxsaylı cihaz bağlantısı üçün ideal seçimdir.

Texniki göstəricilər

WiFi6 WIFI	**Dual band** Genişlik
Mesh Mesh	**2.4Ghz/5Ghz** Tezlik
1000 mb/s Port sürəti	**100+** Qoşulma sayı

Ətraflı məlumat

WIRELESS	
Standards	**Wi-Fi 6** IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	**AX1500** 5 GHz: 1201 Mbps (802.11ax) 2.4 GHz: 300 Mbps (802.11n)
WiFi Range	**3 Bedroom Houses**4× Fixed Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas Beamforming Concentrates wireless signal strength towards clients to expand WiFi range High-Power FEM Improves transmission power to strengthen signal coverage
WiFi Capacity	**High**Dual-Band Allocate devices to different bands for optimal performance OFDMA Simultaneously communicates with multiple Wi-Fi 6 clients Airtime Fairness Improves network efficiency by limiting excessive occupation DFS Access an extra band to reduce congestion 4 Streams Connect your devices to more bandwidth
Working Modes	Router Mode Access Point Mode

SECURITY

Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network
VPN Server	OpenVPN PPTP
WiFi Encryption	WPA WPA2 WPA3 WPA/WPA2-Enterprise (802.1x)

HARDWARE	
Ethernet Ports	1× Gigabit WAN Port 4× Gigabit LAN Ports
Buttons	WPS/Wi-Fi Button Power On/Off Button Reset Button
Power	12 V 1 A

SOFTWARE	
Protocols	IPv4 IPv6
OneMesh™	OneMesh™ Supported Without replacing your existing devices or buying a whole new WiFi ecosystem, OneMesh™ helps you create a more flexible network that covers your entire home with TP-Link OneMesh™ products.
Parental Controls	URL Filtering Time Controls
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP

SOFTWARE	
Quality of Service	QoS by Device
Cloud Service	Auto Firmware Upgrade OTA Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding Port Triggering DMZ UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link NO-IP DynDNS
Management	Tether App Webpage

OTHER	
System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC, CE, RoHS
Environment	Operating Temperature: 0℃~40℃ (32℉ ~104℉) Storage Temperature: -40℃~70℃ (-40℉ ~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

TEST DATA	
WiFi Transmission Power	CE: <20dBm(2.4 GHz) <23dBm(5.15 GHz~5.25 GHz) FCC: <30dBm(2.4 GHz & 5.15 GHz~5.825 GHz)
WiFi Reception Sensitivity	5 GHz: 11a 6Mbps:-97dBm, 11a 54Mbps:-79dBm 11ac VHT20_MCS0:-96dBm, 11ac VHT20_MCS11:-66dBm 11ac VHT40_MCS0:-94dBm, 11ac VHT40_MCS11:-63dBm 11ac VHT80_MCS0:-91dBm, 11ac VHT80_MCS11:-60dBm 11ax HE20_MCS0:-95dBm, 11ax HE20_MCS11:-63dBm 11ax HE40_MCS0:-92dBm, 11ax HE40_MCS11:-60dBm 11ax HE80_MCS0:-89dBm, 11ax HE80_MCS11:-58dBm 2.4 GHz: 11g 6Mbps:-91dBm, 11a 54Mbps:-74dBm 11n HT20_MCS0:-90dBm, 11n HT20_MCS7:-73dBm 11n HT40_MCS0:-88dBm, 11n HT40_MCS7:-70dBm

PHYSICAL	
Dimensions (W×D×H)	10.2 × 5.3 ×1.5 in (260.2 × 135.0 × 38.6 mm)
Package Contents	Wi-Fi Router Archer AX10 Power Adapter RJ45 Ethernet Cable Quick Installation Guide

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az