

CUDY

C200P

Kod: 00-00005566 · Routerlər



Cudy C200P 2-in-1 SMB Router və AP Controller kiçik və orta bizneslər üçün nəzərdə tutulmuş peşəkar şəbəkə həllidir. 4 PoE+ port vasitəsilə access point və IP cihazların birbaşa qidalanmasını dəstəkləyir. Mərkəzləşdirilmiş idarəetmə, stabil performans və asan qurulum təqdim edir.

Texniki göstəricilər



Cloud Controller

Tip



1000 mb/s

Port sürəti

Ətraflı məlumat

Model	C200P 1.0
CPU Details	880 MHz Dual-Core
Flash/ROM	16 MB (128 Mbit) NOR
DDR/RAM	256 MB (2 Gbit) DDR3
Gigabit RJ45 Ports	5
Gigabit RJ45 PoE Ports	#2~#5
Max Power on a Single PoE Ports	30W
PoE Ports Notes	The PoE ports comply with IEEE 802.3at/af standards.
Ethernet Notes	1× WAN Port, 4× LAN Ports
USB-A 3.0 Ports	1
LED	• System • PoE Max Status • Link/ACT/PoE Status of Each PoE Port
Physical Buttons	Reset Button
Power Input	DC Jack
Power Methods	• DC • 802.3at/af PoE • Passive PoE
DC	54V 1.11A
Passive PoE	24/48V
Power Adapter	Input: 100 ~ 240 V, 50 Hz AC Output: 54V 1.11A DC
Max Power Consumption (W)	Total: 60W PoE: 55W PoE (when USB Device is plugged in): 50W No PoE: 5W
Idle Power Consumption (W)	2W

EMS	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV
Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~104 °F) Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F) Operating Humidity: 5% ~ 95% non-condensing Storage Humidity: 0% ~ 100% non-condensing
Grounding Methods	Grounding Point
FCC, CE	
Installation	• Desktop • Wall-mount
Casing Material	Metal
Dimension	190×100×28 mm 7.48×3.94×1.1 inches
• C200P • Power Adapter • Ethernet Cable • Installation Guide • Mounting Kit	
Retail Package Dimension	209×132×81.5 mm 8.23×5.2×3.21 inches
Units per Carton	10
Carton Dimension	43.8×42.8×15.1 cm 17.24×16.85×5.94 inches
WAN Mode	• DHCP • Static IP • PPPOE
Recommended Number of APs	1. Main Router and AP Controller Mode: 10 2. AP Controller Mode: 200* * If using the external portal server feature, it is recommended to manage fewer than 200 APs.
Recommended Number of Clients	1. Main Router and AP Controller Mode: 100 2. AP Controller Mode: Not limited by controller
QoS	Rate Limiting

DHCP	• Address Reservation • DHCP Client List • Server
IP Versions	IPv4/IPv6
IPv6 Protocols	• Relay • Dynamic (SLAAC/DHCPv6) • Static (Fixed IP) • Passthrough • 464XLAT • MAP-E • DS-Lite
TTL Customization	• Extend • Spoof • Custom
IGMP	• IGMP Proxy • IGMP Snooping
Forwarding	• Port Forwarding • Port Triggering • UPnP • DMZ
Firewall	• SPI Firewall • DoS Protection • Block PING
Application Layer Gateway	• IPSec Passthrough • L2TP Passthrough • PPTP Passthrough • FTP Passthrough • TFTP Passthrough • H323 Passthrough • SIP Passthrough • RTSP Passthrough

VPN Server	• WireGuard • OpenVPN • IPsec • Zerotier • PPTP • L2TP
VPN Client	• WireGuard • OpenVPN • IPsec • Zerotier • PPTP • L2TP
VPN Performance	• OpenVPN Client (UL/DL): 22 / 24.7 Mbps • OpenVPN Server (UL/DL): 22 / 20.9 Mbps • WireGuard Client (UL/DL): 142 / 233.9 Mbps • WireGuard Server (UL/DL): 213 / 152 Mbps
Max Concurrent VPN Tunnels	• IPSec: 20 • PPTP/L2TP: 16 • OpenVPN: 16
DNS Options	• DNS over TLS • Manual DNS • Rebind Protection • Override Clients' DNS
DNS over TLS Providers	• Cloudflare • Google • Quad9 • Custom
USB Functions	Samba Server
Wake on LAN	True
Online Detection	True

All Devices Management	• Wi-Fi Time Schedule • MAC Filter • IP/MAC Binding
Per-Devices Management	• Internet On/Off • VPN On/Off • Online Time Schedule • Device Rename
Content Management	• Domain Filter • IP Filter
AP Management	Captive Portal, Multi-SSID (Up to 4 SSIDs on each band)
Local Control Method	Config Web Page
Remote Control Method	• Config Page via HTTPS • TR069/TR098/TR111/TR143/TR181
Firmware Upgrade	Local Update
Reliability	• Timed Reboot • Backup and Restore
Diagnostic Tools	• Diagnosis • Ping • Traceroute • NSLookup • System Log
Panel	• Internet Status • WAN Status • LAN Status • VPN Status • DHCP Server Status • System Version • AP Management

Languages

- English
- Bengali
- Catalan
- Czech
- German
- Greek
- Spanish
- French
- Hebrew
- Croatian
- Hungarian
- Italian
- Japanese
- Khmer
- Korean
- Dutch
- Norwegian
- Polish
- Portuguese
- Romanian
- Russian
- Slovak
- Swedish
- Thai
- Turkish
- Ukrainian
- Vietnamese
- Simplified Chinese

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az