MIKROTIK

C53UIG+5HPaxD2HPaxD (HAP AX3)

Kod: 00-00004305 · Access Pointlər



MIKROTIK HAP AX3 (C53UIG+5HPaxD2HPaxD)

Texniki göstəricilər

WiFi6
WIFI

Dual band
Genişlik

PoE
PoE

2.4Ghz/5Ghz
Tezlik

Ətraflı məlumat

Details	
Product code	C53UiG+5HPaxD2HPaxD
Architecture	ARM 64bit
CPU	IPQ-6010
CPU core count	4
CPU nominal frequency	auto (864 - 1800) MHz
Switch chip model	IPQ-6010
RouterOS license	6
Operating System	RouterOS v7
Size of RAM	1 GB
Storage size	128 MB
Storage type	NAND
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-40°C to 70°C
IPsec hardware acceleration	Yes
Wireless 2.4 GHz Max data rate	574 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n/ax
Antenna gain dBi for 2.4 GHz	3.3
Wireless 2.4 GHz chip model	QCN-5022
Wireless 2.4 GHz generation	Wi-Fi 6
Wireless 5 GHz Max data rate	1200 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac/ax
Antenna gain dBi for 5 GHz	5.5

Details	
Wireless 5 GHz chip model	QCN-5052
Wireless 5 GHz generation	Wi-Fi 6
WiFi speed	AX1800
10/100/1000 Ethernet ports	4
Number of 1G Ethernet ports with PoE-out	1
Number of 2.5G Ethernet ports	1
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB 3.0 type A
Max USB current (A)	1
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-28 V
Max power consumption	38 W
Max power consumption without attachments	15 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	18-28 V
PoE-out ports	Ether 1
PoE out	Passive PoE
Max out per port output (input 18-30 V)	0.625 A
Max total out (A)	0.625 A
Total output current	0.625
Total output power	15

Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	20
CPU temperature monitor	Yes
Mode button	Yes

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az