EZVIZ

C6N

Kod: 00-00003006 · Wifi kamera



EZVIZ C6N ikitərəfli səsli PT wifi kamera. Motion Detection, Smart Tracking

Texniki göstəricilər

2 MP Meqapixel	**10m** Gecə görmə məsafəsi
İkitərəfli səs Səs	**256Gb** Micro SD
Wifi Qoşulma	**Indoor** İş mühiti

Ətraflı məlumat

Model	CS-C6N-A0-1C2WFR
Image Sensor	1/4" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm@ F2.4, view angle: 85° diagonal, 75° horizontal, 45° vertical
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
Video Compression	H.264
Video Bit Rate	Full HD, HD, Standard. Adaptive bit rate.
Max. Resolution	1920 × 1080
Frame Rate	Max. 15fps; Self-adaptive during network transmission
Smart Alarm	Motion detection
Wi-Fi Pairing	AP Pairing
Protocol	EZVIZ Cloud Proprietary Protocol
Interface Protocol	EZVIZ Cloud Proprietary Protocol
Storage	MicroSD card slot (Max. 256 GB)
Power	Micro USB
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)
Standard	IEEE802.11 b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 72 Mbps
Power Supply	DC 5V/1A
Power Consumption	5W max

IR Range	MAX. 10m (32.81 fts)
Dimensions	88 mm x 88.2 mm x 119 mm (3.46” x 3.47” x 4.69”)
Packaging Dimensions	103 mm x 103 mm x 168 mm (4.06” x 4.06” x 6.61”)
Bare Weight	218g (0.48lb)
Packaging Contents	C6N camera; Base; Screw Kit; Power Cable 3m (9.8 ft.); Drill Template; Power Adapter; Quick Start Guide
Temperature	-10° C to 45° C (14° F to 113° F)
Humidity	95% or less (non-condensing)
Certifications	FCC / UL / CE / WEEE / REACH / RoHS

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az