MIKROTIK

cAP ac (RBcAPGI-5acD2ND)

Kod: 00-00001151 · Access Pointlər



MikroTik cAP ac (RBcAPGi-5acD2nD), dual-band (2.4 GHz və 5 GHz) dəstəyi, 2 gigabit port və PoE ilə qidalanma imkanına sahib tavana montaj olunan Wi-Fi access point-dir. Ofis, kafe və ictimai məkanlar üçün ideal şəbəkə həllidir. Kompakt və estetik dizaynı ilə həm texniki, həm də vizual baxımdan üstünlük yaradır.

Texniki göstəricilər

WiFi5 WIFI	**Dual band** Genişlik
PoE PoE	**2.4Ghz/5Ghz** Tezlik
100+ Qoşulma sayı	

Ətraflı məlumat

Details	
Product code	RBcAPGi-5acD2nD
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	488-896 (auto) MHz
Switch chip model	IPQ-4018
Dimensions	Round case: ⌀ 136 mm, height: 30 mm; Square case: 145 mm x 145 mm x 30 mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 50°C
IPsec hardware acceleration	Yes
Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2
Wireless 2.4 GHz chip model	IPQ-4018
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2

Details	
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	2.5
Wireless 5 GHz chip model	IPQ-4018
Wireless 5 GHz generation	Wi-Fi 5
WiFi speed	AC1200
Details	
10/100/1000 Ethernet ports	2
Details	
Number of DC inputs	1 (PoE-IN)
Max power consumption	24 W
Max power consumption without attachments	12 W
Cooling type	Passive
PoE in	802.3af/at
PoE in input Voltage	17-57 V
Details	
PoE-out ports	Ether2
PoE out	Passive PoE up to 57V
Max out per port output (input 18-30 V)	500 mA
Max out per port output (input 30-57 V)	400 mA
Max total out (A)	500 mA
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	20
Details	
Mode button	Yes

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az