

CH3-WCA

TENDA CH3-WCA 2MP OUTDOOR FULL COLOR PT WiFi CAMERA (N). Xarici Wi-Fi Pan/Tilt Kamera CH3-WCA, 360° vizual əhatə dairəsi, Tam rəngli gecə görmə, 1080P ayırdetmə videosu, tam dupleks ikitərəfli audio, insan aşkarlanması, səsi birləşdirən yüksək performanslı açıq hava müşahidə kamerasıdır. və işıq signalı funksiyaları.



Model	CH3-WCA
Brend	Tenda
Internet	Wifi
Meqapixel	2 MP
Gecə görmə məsafəsi	30m
Səs	İkitərəfli səs
Micro SD	256Gb

Specification

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	/
Focal Length	4 mm
Aperture	F1.6
FOV	Horizontal FOV: 85.6°, Vertical FOV: 55.3°, Diagonal FOV: 93.1°
Supplementary Light	2 IR Lights, 2 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode
Video Encoding Format	H.264
Main Stream Resolution	1920 × 1080, 1280 × 720
Sub Stream Resolution	640 × 360
Frame Rate	1-15fps, Default 15fps
Bit Rate	256kbps -- 8192kbps
Bit Rate Control	CBR, VBR
Audio Encoding Format	G.711A

Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Dual external antennas
Wireless Standard	IEEE 802.11 b/g/n
Transmission Rate	Up to 300 Mbps
Channel Width	20/40 MHz
Modulation	DSSS/OFDM
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.08W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Smart Detection	Motion Detection, Human Detection
Smart Linkage	Sound&light Alert, Human Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 256 GB
Reset Button	Support
LED Indicator	Dual Color (red & blue) LED Indicator
Power	12 V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Smart Integration	Amazon Alexa
Product Dimension	138 mm x 120 mm x 187 mm (5.4 x 4.7 x 7.4)
Package Dimension	167 mm x 131 mm x 251 mm (6.6 x 5.2 x 9.9)
Product Weight	426g (0.94lb)
With Package Weight	840g (1.85lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Waterproof Kit Quick Installation Guide