

CH3-WCA

TENDA CH3-WCA 2MP OUTDOOR FULL COLOR PT WiFi CAMERA (N). Xarici Wi-Fi Pan/Tilt Kamera CH3-WCA, 360° vizual əhatə dairəsi, Tam rəngli gecə görmə, 1080P ayırdetmə videosu, tam dupleks ikitərəfli audio, insan aşkarlanması, səsi birləşdirən yüksək performanslı açıq hava müşahidə kamerasıdır. və işıq siqnalı funksiyaları.



Specifications

Model	CH3-WCA
Brand	Tenda
Qoʻulma	Wifi
Meqapixel	2 MP
Gecə görmə m?saf?si	30m
S?s	İkitərəfli səs
Micro SD	256Gb
?? mühiti	Outdoor

KEY FEATURES

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	/
Focal Length	4 mm
Aperture	F1.6
FOV	Horizontal FOV: 85.6°, Vertical FOV: 55.3°, Diagonal FOV: 93.1°
Supplementary Light	2 IR Lights, 2 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode
Video Encoding Format	H.264
Main Stream Resolution	1920 × 1080, 1280 × 720
Sub Stream Resolution	640 × 360
Frame Rate	1-15fps, Default 15fps
Bit Rate	256kbps -- 8192kbps
Bit Rate Control	CBR,VBR
Audio Encoding Format	G.711A
Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Dual external antennas
Wireless Standard	IEEE 802.11 b/g/n
Transmission Rate	Up to 300 Mbps
Channel Width	20/40 MHz
Modulation	DSSS/OFDM
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.08W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Smart Detection	Motion Detection, Human Detection
Smart Linkage	Sound&light Alert, Human Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker

Storage	Built-in Micro SD Card Slot, Up to 256 GB
Reset Button	Support
LED Indicator	Dual Color (red & blue) LED Indicator
Power	12 V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Smart Integration	Amazon Alexa
Product Dimension	138 mm x 120 mm x 187 mm (5.4 × 4.7 × 7.4)
Package Dimension	167 mm x 131 mm x 251 mm (6.6 × 5.2 × 9.9)
Product Weight	426g (0.94lb)
With Package Weight	840g (1.85lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Waterproof Kit Quick Installation Guide