

CH7-WCA

TENDA CH7-WCA 4MP OUTDOOR FULL COLOR PT WiFi CAMERA (N). Xarici Wi-Fi Pan/Tilt Kamera CH7-WCA, 360° vizual əhatə dairəsi Tam Rəngli gecə görmə 4MP təsvir ölçülü video, tam duplex ikitərəfli audio, insan aşkarlanması, avtomobili birləşdirən yüksək performanslı açıq hava müşahidə kamerasıdır. aşkarlama, səs və işıq signalizasiya funksiyaları.



Model	CH7-WCA
Brend	Tenda
Internet	Wifi
Meqapixel	4 MP
Gecə görmə məsafəsi	30m
Səs	İkitərəfli səs
Micro SD	256Gb

Specification

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	/
Focal Length	4 mm
Aperture	F1.6
FOV	Horizontal FOV: 83°, Vertical FOV: 44°, Diagonal FOV: 98.6°
Supplementary Light	2 IR Lights, 2 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode
Video Encoding Format	H.265, H.264
Main Stream Resolution	2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720
Sub Stream Resolution	640 x 360, 352 x 288
Frame Rate	1-30fps, Default 20fps
Bit Rate	512kbps -- 4096kbps
Bit Rate Control	CBR,VBR
Audio Encoding Format	G.711A, G.711U, AAC

Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, BLC, HLC, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP, WebSockets
Web Browser	Plug-in free live view: Chrome, Edge, Opera
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Dual external antennas
Wireless Standard	IEEE 802.11 b/g/n
Transmission Rate	Up to 300 Mbps
Channel Width	20/40 MHz
Modulation	DSSS/OFDM
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.092W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Smart Detection	Motion Detection, Tempering Detection, Human Detection, Vehicle Detection
Smart Linkage	Sound&light Alert, Human Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 256 GB
Reset Button	Support
LED Indicator	Dual Color (red & blue) LED Indicator
Power	12 V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Smart Integration	Amazon Alexa
Product Dimension	138 mm x 120 mm x 187 mm (5.4 x 4.7 x 7.4)
Package Dimension	167 mm x 131 mm x 251 mm (6.6 x 5.2 x 9.9)
Product Weight	426g (0.94lb)
With Package Weight	840g (1.85lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Waterproof Kit Quick Installation Guide