

CH9-WCA

TENDA CH9-WCA 3MP+3MP DUAL OUTDOOR FULL COLOR PT WiFi CAMERA (N) İkili obyektivli a ıq Wi-Fi pan/ ym  kamerası CH9-WCA, 6MP t svir  l l  video (3MP+3MP), 360  vizual  hat  dair si, tam r ngli gec  g rm , tam dupeks birl şdir n y ks k performanslı a ıq t hl k sizlik kamerasıdır. İkit r fli audio, insan a karlanması, avtomobilin a karlanması, xəttin k şim sinin a karlanması, m daxil nin a karlanması, ikili obyektivli ağıllı  laq , s s v  i ıq signalı funksiyaları.



Specifications

Model	CH9-WCA
Brand	Tenda
Meqapixel	3 MP
Gec� g�rm� m�saf�si	30m
S�s	İkit�r�fli s�s
Micro SD	512Gb
Qo�ulma	Wifi
�� m�hiti	Outdoor

KEY FEATURES

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	Pan 0° to 260°
Focal Length	Fixed Lens 4mm PT Lens 6mm
Aperture	Fixed Lens F1.6 PT Lens F1.6
FOV	Fixed Lens Horizontal FOV: 82.3°, Vertical FOV: 44.7°, Diagonal FOV: 97.4° PT Lens Horizontal FOV: 51.8°, Vertical FOV: 28.2°, Diagonal FOV: 60.4°
Supplementary Light	6 IR Lights, 6 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode
Video Encoding Format	Fixed Lens H.265, H.264 PT Lens H.265, H.264
Main Stream Resolution	Fixed Lens 2304 × 1296, 1920 × 1080, 1280 × 720 PT Lens 2304 × 1296, 1920 × 1080, 1280 × 720
Sub Stream Resolution	Fixed Lens 640 × 360 PT Lens 640 × 360
Frame Rate	Fixed Lens 1-25fps (2304 × 1296 1-18fps), Default 18fps PT Lens 1-25fps (2304 × 1296 1-18fps), Default 18fps
Bit Rate	Fixed Lens 512kbps -- 4096kbps PT Lens 512kbps -- 4096kbps
Bit Rate Control	Fixed Lens CBR, VBR PT Lens CBR, VBR
Audio Encoding Format	G.711A, G.711U, AAC
Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, BLC, HLC, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP, WebSockets
Web Browser	Plug-in free live view: Chrome, Edge, Opera
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Internal antenna
Wireless Standard	IEEE 802.11 b/g/n/ax
Transmission Rate	Up to 287Mbps

Channel Width	20/40 MHz
Modulation	DSSS/OFDM/OFDMA
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.1W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3-SAE
Smart Detection	Both fixed lens and PT lens are supported motion detection, human detection, vehicle detection, line crossing Detection, intrusion detection
Smart Linkage	Sound&light Alert, Dual-lens Linkage Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 512 GB
Reset Button	Support
LED Indicator	Dual Color(red & blue) LED Indicator
Power	12V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Product Dimension	203mm x 122mm x 62mm(8.0 x 4.8 x 2.4)
Package Dimension	240mm x 145mm x 193mm(9.4 x 5.7 x 7.6)
Product Weight	527g(1.16lb)
With Package Weight	802g(1.77lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Waterproof Kit Quick Installation Guide