

# CH9-WCA

TENDA CH9-WCA 3MP+3MP DUAL OUTDOOR FULL COLOR PT WiFi CAMERA ( N ) İkilı obyektivli aıq Wi-Fi pan/əymə kamerası CH9-WCA, 6MP təsvir ölçülü video (3MP+3MP), 360° vizual əhatə dairəsi, tam rəngli gecə görmə, tam duplex birləşdirən yüksək performanslı aıq təhlükəsizlik kamerasıdır. İkitərəfli audio, insan aşkarlanması, avtomobilin aşkarlanması, xəttin kəsişməsinin aşkarlanması, müdaxilənin aşkarlanması, ikili obyektivli ağıllı əlaqə, səs və işıq signalı funksiyaları.



Model	CH9-WCA
Brend	Tenda
Internet	Wifi
Meqapixel	3 MP
Gecə görmə məsafəsi	30m
Səs	İkitərəfli səs
Micro SD	512Gb

## Specification

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	Pan:0°to 260°
Focal Length	Fixed Lens:4mm PT Lens:6mm
Aperture	Fixed Lens:F1.6 PT Lens:F1.6
FOV	Fixed Lens: Horizontal FOV: 82.3°, Vertical FOV: 44.7°, Diagonal FOV: 97.4° PT Lens: Horizontal FOV: 51.8°, Vertical FOV: 28.2°, Diagonal FOV: 60.4°
Supplementary Light	6 IR Lights, 6 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode

Video Encoding Format	Fixed Lens:H.265, H.264 PT Lens:H.265, H.264
Main Stream Resolution	Fixed Lens:2304 ×1296, 1920 × 1080, 1280 × 720 PT Lens:2304 ×1296, 1920 × 1080, 1280 × 720
Sub Stream Resolution	Fixed Lens:640 × 360 PT Lens:640 × 360
Frame Rate	Fixed Lens:1-25fps (2304 × 1296 1-18fps), Default 18fps PT Lens:1-25fps (2304 × 1296 1-18fps), Default 18fps
Bit Rate	Fixed Lens:512kbps -- 4096kbps PT Lens:512kbps -- 4096kbps
Bit Rate Control	Fixed Lens:CBR,VBR PT Lens:CBR,VBR
Audio Encoding Format	G.711A, G.711U, AAC
Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, BLC, HLC, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP, WebSockets
Web Browser	Plug-in free live view: Chrome, Edge, Opera
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Internal antenna
Wireless Standard	IEEE 802.11 b/g/n/ax
Transmission Rate	Up to 287Mbps
Channel Width	20/40 MHz
Modulation	DSSS/OFDM/OFDMA
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.1W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3-SAE
Smart Detection	Both fixed lens and PT lens are supported motion detection, human detection, vehicle detection, line crossing Detection, intrusion detection
Smart Linkage	Sound&light Alert, Dual-lens Linkage Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 512 GB
Reset Button	Support
LED Indicator	Dual Color(red & blue) LED Indicator
Power	12V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Product Dimension	203mm x 122mm x 62mm(8.0 ×4.8 × 2.4)
Package Dimension	240mm x 145mm x 193mm(9.4 ×5.7 × 7.6)
Product Weight	527g(1.16lb)
With Package Weight	802g(1.77lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)

Humidity	<b>Operating Humidity: 10% ~ 95% RH (non-condensing)</b> <b>Storage Humidity: 3% ~ 95% RH (non-condensing)</b>
Package Contents	<b>Camera</b> <b>Power Adapter (cord length: 3m)</b> <b>Installation Template</b> <b>Mounting Bracket</b> <b>Mounting Accessories Kit</b> <b>Waterproof Kit</b> <b>Quick Installation Guide</b>