

CP3

TENDA CP3 2MP WiFi CAMERA (N). Təhlükəsizlik Pan/Tilt Kamerası CP3V2.2 360° panoramik əhatə dairəsi, 3MP HD piksel, tam duplex ikitərəfli audio interkom, hərəkət izləmə və DIY audio funksiyalarını özündə birləşdirən kameradır.



Specifications

Model	CP3
Brand	Tenda
Qoʻulma	Wifi
Meqapixel	2 MP
Gec? görm? m?saf?si	10m
S?s	Mikrofon
Micro SD	256Gb
?? mühiti	Indoor

KEY FEATURES

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	/
Focal Length	4mm
Aperture	F2.2
FOV	Horizontal : 79.4°, Vertical : 48°, Diagonal : 87°
Supplementary Light	4 IR Lights
Supplementary Light Distance	Up to 10 m/32 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Black & White Mode
Video Encoding Format	H.264
Main Stream Resolution	1920 × 1080, 1280 × 720
Sub Stream Resolution	640 x 360
Frame Rate	1-15fps,Default 15fps
Bit Rate	256kbps -- 8192kbps
Bit Rate Control	VBR
Audio Encoding Format	G.711A
Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio
Image Enhancement	DWDR, 3D DNR
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP
Pan Movement Range	0°--355°
Tilt Movement Range	-65°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Internal antenna
Wireless Standard	IEEE 802.11 b/g/n
Transmission Rate	Up to 144Mbps
Channel Width	20 MHz
Modulation	DSSS/OFDM
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.062W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Smart Detection	Motion Detection, Human Detection
Smart Linkage	Sound&light Alert, Human Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 256 GB
Reset Button	Support

LED Indicator	Dual Color (red & blue) LED Indicator
Power	9V DC, 1A, Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Smart Integration	Amazon Alexa
Product Dimension	103mm x 88mm x 88mm (4.1 ×3.5 × 3.5)
Package Dimension	100mm x 100mm x 165mm (4.0 ×4.0 × 6.5)
Product Weight	206g (0.46lb)
With Package Weight	390g (0.86lb)
Installation Method	Desktop, Ceiling Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -10°C ~ 45°C (14°F ~ 113°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Quick Installation Guide