

CRS326-24G-2S+RM

Mikrotik CRS326-24G-2S+RM. 24 Gigabit port, 2 x SFP+, DualBoot(RouterOS və ya SwitchOS), 1U rackmount



| | |
|-------------|------------------|
| Model | CRS326-24G-2S+RM |
| Brend | Mikrotik |
| Port sayı | 24 Port |
| Tip | Smart |
| Port sürəti | 1000mb/s |

Specification

Specifications

| Details | |
|----------------------------|------------------------------------|
| Product code | CRS326-24G-2S+RM |
| Architecture | ARM 32bit |
| CPU | 98DX3236 |
| CPU core count | 1 |
| CPU nominal frequency | 800 MHz |
| Switch chip model | 98DX3236 |
| Dimensions | 443 x 144 x 44 mm |
| RouterOS license | 5 |
| Operating System | RouterOS / SwitchOS |
| Size of RAM | 512 MB |
| Storage size | 16 MB |
| Storage type | FLASH |
| MTBF | Approximately 200'000 hours at 25C |
| Tested ambient temperature | -40°C to 60°C |

Powering

| Details | |
|-----------------------|---------------------|
| Number of DC inputs | 2 (DC jack, PoE-IN) |
| DC jack input Voltage | 10-30 V |
| Max power consumption | 24 W |
| Cooling type | Passive |
| PoE in | Passive PoE |
| PoE in input Voltage | 10-30 V |

Ethernet

| Details | |
|----------------------------|----|
| 10/100/1000 Ethernet ports | 24 |

Fiber

| Details | |
|------------|---|
| SFP+ ports | 2 |

Peripherals

| Details | |
|---------------------|------|
| Serial console port | RJ45 |

Certification & Approvals

| Details | |
|---------------|---------------|
| Certification | CE, EAC, ROHS |
| IP | IP20 |