CS-C8PF-A0-6E22WFR

EZVIZ CS-C8PF-A0-6E22WFR(2.8MM)(12MM) 2mp IR 30m Dual-Lens 8× Mixed Zoom 2-Way Talk Outdoor PTZ 512Gb Micro Card

Specifications

Model	CS-C8PF-A0-6E22WFR
Brand	Ezviz
Meqapixel	2 MP
Gec? görm? m?saf?si	30m
S?s	İkitərəfli səs
Micro SD	512Gb
Qo?ulma	Wifi
?? mühiti	Outdoor

KEY FEATURES

Model	CS-C8PF (1080P)
Image sensor	Dual-1/2.7" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8 mm @ F1.6 + 12 mm @ F1.6
PT Angle	Pan: 340°, Tilt: 80°
Minimum Illumination	0.05Lux @ (F1.6 AGC ON), 0 Lux with IR
Lens Mount	M12
Day & Night	IR-cut filter with auto switching
DNR	3D DNR
WDR	Digital WDR
BLC	Supports
Black & White Night	30 m/ 98 ft
Max Resolution	1920 × 1080
Frame Rate	Max. 15fps, self-adaptive during network transmission
Video Compression	H.265 / H.264
H.265 Type	Main profile
Video Bit Rate	Full HD; HD; Standard. Adaptive bit rate.
Audio Bit Rate	Self-Adaptive
Max. Bitrate	2Mbps
Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :72Mbps
Wi-Fi Pairing	AP pairing
Protocol	EZVIZ Cloud Proprietary Protocol
Interface Protocol	EZVIZ Cloud Proprietary Protocol
Wired Network	RJ45 × 1(10M/100M Adaptive Ethernet Port)
Smart Alarm	AI-powered Human Shape Detection
Customized Alert Area	Supports
Audio	Supports mic
General Function	Anti-flicker, dual-stream, heart beat, password protection, watermark
Local Storage	MicroSD card slot (Max. 512GB)
Cloud Storage	EZVIZ cloud storage
Operating Conditions	-30°C to 60°C (14°F to 113°F), humidity 95% or less (non-condensing)
IP Grade	Weatherproof design
Power Supply	DC 12V / 1A
Power Consumption	MAX. 12W
Dimensions	154 × 116 × 164 mm (6.06 × 4.57 × 6.46 inch)
Packaging Dimensions	197 × 185 × 205 mm (7.76 × 7.28 × 8.07 inch)
Weight	Product: 578 g (20.39 oz)

With package: 938 g (33.09 oz)

In the box	- C8PF Camera
	- 1.5-Meter Power Adapter
	- Screw Kit
	- Waterproof Kit
	- Drill Template
	- Regulatory Information
	- Quick Start Guide
Certifications	UL / FCC / CE / WEEE / REACH/ ROHS

With package: 938 g (33.09 oz)

- C8PF Camera

- 1.5-Meter Power Adapter