EZVIZ

CS-H8-R100-1J5WKFL

Kod: 00-00003918 · Wifi kamera



EZVIZ CS-H8-R100-1J5WKFL(4MM) 3K 5mp LED 30m Color Night Vision WiFi Outdoor PT Kamera EZVIZ H8 Pro 3K (5MP) Wi-Fi PT kamera. 360° kor nöqtəsiz izləmə, rəngli gecə görüşü və süni intellektli insan/nəqliyyat aşkarlanması. Aktiv müdafiə (sirena/işıq), ikitərəfli səs, əl hərəkəti ilə zəng və 512GB kart dəstəyi. IP65 suya davamlı korpus.

Texniki göstəricilər

5 MP Meqapixel	**Wifi** Qoşulma
30m Gecə görmə məsafəsi	**İkitərəfli səs** Səs
512Gb Micro SD	**Outdoor** İş mühiti

Ətraflı məlumat

Model	CS-H8-R100-1J5WKFL
Image Sensor	1/2.7" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm@ F1.6, Viewing angle: 46° (Vertica), 89° (Horizontal), 104° (Diagonal) 6mm@ F1.6, Viewing angle:28° (Vertica), 54° (Horizontal), 62° (Diagonal)
PT Angle	Pan: 340°, Tilt: 80°
Minimum Illumination	0.5 Lux @ (F1.6, AGC ON), 0 Lux with IR (Data is obtained from EZVIZ laboratories)
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
Night Vision Distance	Up to 30m / 98ft
Max. Resolution	2880 × 1620
Frame Rate	Max:30fps; Self-Adaptive during network transmission
Video Compression	H.265 / H.264
H.265 Type	Main Profile
Video Bit Rate	Quad HD+; Full HD; Hi-Def; Standard. Adaptive bit rate.
Audio Bit Rate	Self-Adaptive
Max. Bitrate	4 Mbps
Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20 MHz
Security	WPA-PSK / WPA2-PSK

Transmission Rate	11b 11Mbps, 11g 54Mbps, 11n 72Mbps
Wi-Fi Pairing	AP pairing
Protocol	EZVIZ Cloud Proprietary Protocol
Interface Protocol	EZVIZ Cloud Proprietary Protocol
Wired Network	RJ45 × 1(10M / 100M Adaptive Ethernet Port)
Local Storage	Supports Micro SD card (Up to 512GB)
Cloud Storage	Supports EZVIZ CloudPlay storage (Subscription required)
Smart Alarm	AI Powered Human / Vehicle Detection / Waving-Hand Recognition &Control
Auto Tracking	Supports
Customized Alert Area	Supports
Two-way Talk	Supports
General Function	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
Operating Conditions	-30 °C to 50°C (-22 °F to 122 °F), humidity 95% or less (non-condensing)
IP Grade	Weatherproof Design
Power Supply	DC 12V / 1A
Power Consumption	MAX. 6W
Dimensions	116 × 153.2 × 163.8 mm (4.57 × 6.03 × 6.45 inch)
Packaging Dimensions	187 × 174 × 186.5 mm (7.36 × 6.85 × 7.34 inch)
Weight	Net Weight: 592 g (20.88 oz) With Package: 943 g (33.26 oz) For EU Standard Version
In the box	- H8 Pro 3K Camera
	- Power Adapter
	- Screw Kit
	- Waterproof Kit
	- Drilling Template
	- Regulatory Information

- Quick Start Guide	
Certifications	UL / FCC / CE / WEEE / RoHS / UKCA

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az