

CS-H8C

EZVIZ CS-H8C full color (rəngli) ikitərəfli səsli PT wifi kamera. AI-Powered Human Detection.



| | |
|---------------------|----------------|
| Model | CS-H8C |
| Brend | Ezviz |
| Məqapixel | 2 MP |
| Gecə görmə məsafəsi | 30m |
| Səs | İkitərəfli səs |
| Micro SD | 512Gb |

Specification

| | |
|-----------------------|--|
| Model | Model CS-H8c (1080P) |
| Image Sensor | 1/2.7" Progressive Scan CMOS |
| Shutter Speed | Self-adaptive shutter |
| Lens | 4mm @ F2.0, viewing angle: 46° (Vertical), 89° (Horizontal), 104° (Diagonal) |
| PT Angle | Pan: 350°, Tilt: 80° |
| Minimum Illumination | 0.5 Lux @ (F1.6, AGC ON), 0 Lux with IR (Data is obtained from EZVIZ laboratories) |
| Lens Mount | M12 |
| Day & Night | IR-Cut filter with auto-switching |
| DNR | 3D DNR |
| WDR | Digital WDR |
| Night Vision Distance | 30 m / 98 ft |
| Max. Resolution | 1920 × 1080 |
| Frame Rate | Max: 30fps; Self-Adaptive during network transmission |
| Video Compression | H.265 / H.264 |
| H.265 Type | Main Profile |
| Video Bit Rate | Full HD; Hi-Def; Standard. Adaptive bit rate. |
| Audio Bit Rate | Self-Adaptive |
| Max. Bitrate | 2 Mbps |
| Wi-Fi Standard | IEEE802.11b, 802.11g, 802.11n |
| Frequency Range | 2.4 GHz ~ 2.4835 GHz |

| | |
|-----------------------|--|
| Channel Bandwidth | Supports 20 MHz |
| Transmission Rate | 11b: 11 Mbps,11g: 54 Mbps,11n: 72 Mbps |
| Wi-Fi Pairing | AP pairing |
| Protocol | EZVIZ Cloud Proprietary Protocol |
| Interface Protocol | EZVIZ Cloud Proprietary Protocol |
| Wired Network | RJ45 × 1 (10M / 100M Adaptive Ethernet Port) |
| Local Storage | MicroSD card slot (Up to 512GB) |
| Cloud Storage | EZVIZ Cloud Storage (Subscription Required) |
| Smart Alarm | AI-Powered Human Shape Detection |
| Customized Alert Area | Supports |
| Two-way Talk | Supports |
| General Function | Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark |
| Operating Conditions | -30 °C to 50°C (-22 °F to 122 °F), humidity 95% or less (non-condensing) |
| IP Grade | Weatherproof Design |
| Power Supply | DC 12V / 1A |
| Power Consumption | MAX. 12W |
| Dimensions | 100.05 × 129.19 × 149.75 mm (3.94 × 5.09 × 5.9 inch) |
| Packaging Dimensions | 140 × 140 × 192 mm (5.51 × 5.51 × 7.56 inch) |
| Weight (With package) | 730 g (25.75 oz) |
| Net Weight | 420 g (14.8 oz) |