

# CS-H8C 2K (3MP)

EZVIZ CS-H8C 2K full color (rəngli) ikitərəfli səsli PT wifi kamera. AI-Powered Human Detection.



## Specifications

Model	CS-H8C 2K (3MP)
Brand	Ezviz
Qoʻulma	Wifi
Meqapixel	3 MP
Gecʻ görmʻ mʻsafʻsi	30m
Sʻs	İkitərəfli səs
Micro SD	512Gb
ʻʻ mühiti	Outdoor

## KEY FEATURES

<b>Model</b>	CS-H8c (2K)
<b>Image Sensor</b>	1/2.8" Progressive Scan CMOS
<b>Shutter Speed</b>	Self-adaptive shutter
<b>Lens</b>	4mm@ F1.6, viewing angle: 46° (Vertica), 89° (Horizontal), 104° (Diagonal) 6mm@ F1.6, viewing angle:28° (Vertica), 52° (Horizontal), 60° (Diagonal)
<b>PT Angle</b>	Pan: 350°, Tilt: 80°
<b>Minimum Illumination</b>	0.5 Lux @ (F1.6, AGC ON), 0 Lux with IR (Data is obtained from EZVIZ laboratories)
<b>Lens Mount</b>	M12
<b>Day &amp; Night</b>	IR-Cut filter with auto-switching
<b>DNR</b>	3D DNR
<b>WDR</b>	Digital WDR
<b>Night Vision Distance</b>	30 m / 98 ft
<b>Max. Resolution</b>	2304 × 1296
<b>Frame Rate</b>	Max: 30fps; Self-Adaptive during network transmission
<b>Video Compression</b>	H.265 / H.264
<b>H.265 Type</b>	Main Profile
<b>Video Bit Rate</b>	Quad HD; Full HD; Hi-Def; Standard. Adaptive bit rate.
<b>Audio Bit Rate</b>	Self-Adaptive
<b>Max. Bitrate</b>	3 Mbps
<b>Wi-Fi Standard</b>	IEEE802.11b, 802.11g, 802.11n
<b>Frequency Range</b>	2.4 GHz ~ 2.4835 GHz
<b>Channel Bandwidth</b>	Supports 20 MHz
<b>Transmission Rate</b>	11b: 11 Mbps,11g: 54 Mbps,11n: 72 Mbps
<b>Wi-Fi Pairing</b>	AP pairing
<b>Protocol</b>	EZVIZ Cloud Proprietary Protocol
<b>Interface Protocol</b>	EZVIZ Cloud Proprietary Protocol
<b>Wired Network</b>	RJ45 × 1 (10M / 100M Adaptive Ethernet Port)
<b>Local Storage</b>	MicroSD card slot (Up to 512GB)
<b>Cloud Storage</b>	EZVIZ Cloud Storage (Subscription Required)
<b>Smart Alarm</b>	AI-Powered Human Shape Detection
<b>Customized Alert Area</b>	Supports
<b>Two-way Talk</b>	Supports
<b>General Function</b>	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
<b>Preset Locations</b>	Supports
<b>Operating Conditions</b>	-30 °C to 50°C ( -22 °F to 122 °F ), humidity 95% or less (non-condensing)
<b>IP Grade</b>	Weatherproof Design
<b>Power Supply</b>	DC 12V / 1A
<b>Power Consumption</b>	MAX. 12W
<b>Dimensions</b>	100.05 × 129.19 × 149.75 mm (3.94 × 5.09 × 5.9 inch)

---

<b>Packaging Dimensions</b>	<b>140 × 140 × 192 mm (5.51 × 5.51 × 7.56 inch)</b>
<b>Weight (With package)</b>	<b>745 g (26.28 oz) For EU Standard Version</b>
<b>Net Weight</b>	<b>435 g (15.34 oz)</b>
	<b>- H8c 2K Camera</b>
	<b>- Drill Template</b>
	<b>- Screw Kit</b>
<b>In the box</b>	<b>- Waterproof Kit</b>
	<b>- Power Adapter</b>
	<b>- Regulatory Information</b>
	<b>- Quick Start Guide</b>
<b>Certifications</b>	<b>CE / FCC / UKCA / UL / WEEE / RoHS / REACH</b>