EZVIZ

CS-HP7-R105-1W2TFC

Kod: 00-00005078 · Domofon



EZVIZ HP7 2K qapı telefonu interkom və kamera funksiyasını birləşdirir. 2 K (ultra-HD) görüntü, 162° geniş bucaq, 7″ toxunmatik ekran, iki tərəfli danışıq, insan hərəkəti aşkarlanması və RFID açma funksiyasına malikdir. IP-səviyyəli hava müqaviməti və microSD card (512 GB-a qədər) dəstəyi sayəsində rahat və təhlükəsiz ev girişi təcrübəsi yaradır.

Texniki göstəricilər

IP Bağlantı tipi	**KİT** Cihaz
WIFI WIFI	**SD Card** Yaddaş
Plastik Material	

Ətraflı məlumat

Model	CS-HP7-R105-1W2TFC
Image Sensor	1/2.7" Progressive Scan CMOS (Supports low light sensitivity)
Lens	2.0 mm @ F2.2,viewing angle: 162° (Diagonal)
Day & Night	IR-cut filter with auto-switching, 850 nm infrared light × 2 (max. 6m)
Max. Resolution	2048 × 1296
DNR	2D / 3D DNR
Video Compression	H.265 / H.264
Frame Rate	Max: 15fps; Self-Adaptive during network transmission
Connection Method	Wired connection (2-Wired, capable with 4-Wired), digital signal transmission
Transmission Distance	Φ 2 x 0.75mm² , max. 50m Φ 2 x 1.5mm² , max. 100m Twisted pair, max. 120m
Open the door (Gate)	Support 2 wiring ports. 1-10m distance. The intercom panel provides a “dry”-contact connection, without an electric current, to connect to the button for automated gate, gate breaking capacity: 12V / 2A
Unlock (Electric strike plate)	Support 2 wiring ports. 1-10m distance. The electric strike plate or lock that you order must have a mechanical memory; the power supply to the electric strike plate or lock must not exceed 12V / 1.1A, otherwise should do as user manual.
Door Open Methods	1.RFID badge unlock (Badges × 3 pcs) 2.App remote unlock 3.Indoor display unlock
Audio Input	Built-in high-sensitivity microphone
Audio Output	Built-in high-power speaker
Doorbell Button	Yes. The light can be set on or off.
Name Card	Three handwritten name cards in total (one already on the intercom panel). The light can be set on or off.
Terminal	Two wiring ports to connect screen. Two wiring ports to connect gate. Two wiring ports to connect electric strike plate.
Intelligent Alarm	Smart human motion detection, Lingering Detection
Tamper Alarm	Supports

Video Intercom	Long-distance video two-way talk
Operation Conditions	-30°C to 60°C , Humidity 95% or less (non-condensing)
IP Grade	Waterproof, with shield cover
Size	161 × 87 × 20 mm (6.34 × 3.42 × 0.79 inch)
Display size	7” touch screen
Resolution	1024 × 600
Audio Input	Built-in high-sensitivity microphone
Audio Output	Built-in high-power speaker
Button	Screen On / Off Button
Terminal	Two wiring ports to connect 1st outdoor doorbell.
Storage	Supports microSD card up to 512 GB Supports EZVIZ Cloud storage
Protocol	EZVIZ Cloud Proprietary Protocol
Interface Protocol	EZVIZ Cloud Proprietary Protocol
Protocol	EZVIZ Connect Protocol
Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n, 802.11ac
Frequency Range	2.4G: 2.4 GHz ~ 2.4835 GHz 5G: 5.15 GHz ~ 5.25 GHz
Channel Bandwidth	Supports 20MHz
Security	64 / 128-bit WEP,WPA / WPA2, WPA-PSK / WPA2-PSK
Transmission Rate	11b: 11Mbps, 11g: 54Mbps, 11n: 150Mbps, 11ac: 433.3Mbps
Multiple ringtones	Up to 20 ringtones
Functions	Live view, playback, two-way talk, video call
Operation Conditions	-10°C to 45°C, humidity 95% or less (non-condensing)
Weight	Net weight: 855 g (30.16 oz) With package: 1825 g (64.37 oz)
Size	180 × 111 × 15 mm (7.09 × 4.37 × 0.59 inch)
Power Supply	DC 24V / 1A power supply, adaptor (100- 240Vac)
Power Consumption	8W, Max. 24W

In the box	- Monitor
	- Wall Bracket for Monitor
	- Power Adapter for Monitor
	- Drill Template for Monitor
	- Intercom Panel
	- Drill Template for Intercom Panel
	- Screwdriver
	- Badges (×3)
	- Screw Kit (×2)
	- Name Card (×2)
	- Wires and Wire Connectors
	- DC 24V Power Supply Jack Connector Cable
	- Regulatory Information (×2)
	- Quick Start Guide
Certifications	CE / REACH / WEEE / RoHS

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az