CUDY

FS106P

Kod: 00-00005584 · Switchlər



CUDY FS106P 6-Port 10/100M PoE+ switch, 36W ümumi PoE gücü ilə IP kameralar, VoIP telefonlar və digər PoE cihazları üçün ideal seçimdir. Sadə idarəetmə, etibarlı bağlantı və kompakt metal dizayn ofis və kiçik biznes mühitləri üçün mükəmməldir.

Texniki göstəricilər

5 Port
Port sayı

PoE+
PoE

100mb/s
Port sürəti

Ətraflı məlumat

Model	FS1006P 3.0
10/100 Mbps RJ45 Ports	6
10/100 Mbps RJ45 PoE Ports	#1~#4
Max Power on a Single PoE Port	30W
PoE Port Notes	The PoE ports comply with IEEE 802.3at/af standards.
PoE Priority	Intelligent Power Management: Automatically disconnect the lastly powered device when power exceeds budget.
Shielded RJ45 Port	True
Extend Mode Ports	#1~#4
VLAN Mode Ports	#1~#4
LED	• Power • Link/ACT of Each Ethernet Port
Power Interfaces	AC Inlet
Physical Buttons	Default/Extend/VLAN DIP Switch
Physical Buttons Note	The PoE Watchdog feature will attempt to reboot the plugged-in clients that have been inactive for 5 minutes. Please disable the auto-upgrade feature on the client devices.
Copper Speed and Distance	• Cat. 3 or higher cable: 100 meters at 10 Mbps • Cat. 5 or higher cable: 100 meters at 100 Mbps • Cat. 5e or higher cable: 250 meters at 10 Mbps
Copper Speed and Distance Note	250-meter transmission is only available on the Extend Mode ports when the Extend Mode is activated.
MAC Address Table	2048
Max Switching Capacity	1.2 Gbps
Max Forwarding Rate	0.8928 Mpps
Jumbo Frame	2 KB
Packet Buffer	768 Kbit

Power Methods	AC
Power Input	100-240V~ 50/60Hz
Power Supply	65W
Max Power Excluding PoE	1W
802.3 Protocols	• 802.3i 10BASE-T • 802.3u 100BASE-TX • 802.3x Flow Control • 802.3af PoE • 802.3at PoE
PoE Management	Intelligent Power Management
Grounding Methods	• Three-Prong Plug • Grounding Point
EMS	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: 0~40 ℃ (32~104 ℉) Storage Temperature: -40~70℃ (-40~158 ℉) Operating Humidity: 10~90% non-condensing Storage Humidity: 10~95% non-condensing
Dimension	200×118×44 mm 7.87×4.65×1.73 inches
Product Weight	568.5 g (20.05 oz.)
Casing Material	Metal
Installation	• Desktop • Rackmount via Brackets (Brackets not included in the box)
• **FS1006P** • **Power Cord** • **Installation Guide**	
Retail Package Dimension	249×207×60 mm 9.8×8.15×2.36 inches
Retail Package Weight	EU: 947.5 g (33.42 oz.)
Units per Carton	16

Carton Net Weight	EU: 15.2 kg (33.51 lbs)
Carton Gross Weight	EU: 16.1 kg (35.49 lbs)
Carton Dimension	51.4×42.9×27.2 cm 20.24×16.89×10.71 inches

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az