

## DH-C2K-P

Dahua DH-C2K-P, 2.8mm, Indoor Compact Cube, Wi-Fi, IR 30m, Audio, MicroSD, 12VDC/PoE, 2MP Indoor Compact Cube IP kamera olaraq gündəlik istifadə üçün ideal həll təklif edir. 2.8mm sabit obyektiv, Wi-Fi bağlantısı, iki tərəfli audio, IR işıqlandırma (30m), microSD dəstəyi və həm 12VDC, həm də PoE qidalanma imkanları ilə ev və ofis mühafizəsini gücləndirir.



### Specifications

Model	DH-C2K-P
Brand	Dahua
Meqapixel	2 MP
Qo?ulma	Wifi
Gec? görm? m?saf?si	30m
S?s	İkitərəfli səs
Micro SD	256Gb
?? mühiti	Indoor

## KEY FEATURES

## Camera

Image Sensor	1/2.7" CMOS
Max. Resolution	1920 (H) × 1080 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR)
Illuminator Number	1 (IR LED)
Angle Adjustment	Pan: 0° to 360° Tilt: -10° to 100°
Lens Type	Fixed-focal
Focal Length	2.8 mm; 3.6 mm
Max. Aperture	F2.0
Field of View	2.8 mm: H: 101°; V: 54°; D: 119° 3.6 mm: H: 82°; V: 45°; D: 97°

## Intelligence

Human Detection Yes

## Audio and Video

Video Compression H.265; H.264; H.264H; H.264B; MJPEG (Only supported by the sub stream)

Video Frame Rate Main stream: 1920 × 1080@(1-25/30 fps)

Sub stream: 640 × 360@(1-25/30 fps)

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.264: 24 kbps–6144 kbps

H.265: 9 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

WDR Yes

Motion Detection OFF/ON (4 areas, rectangular)

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression PCM; G.711a; G.711Mu

## Network

Network Port RJ-45 (10/100 Base-T)

Wi-Fi IEEE 802.11b/g/n/ax 2.412–2.472 GHz, 2.4 G

Wi-Fi Pairing Bluetooth pairing

Storage Micro SD card (support max. 256 GB)

Management Smart PSS Lite;DMSS

## Software

Mobile Client iOS;Android

## Function

Abnormal Sound Yes

## Alarm

## General

Certifications CE

Power Supply 12 VDC/PoE

---

<b>Power Consumption</b>	<b>Basic: 1.92 W (12 VDC); 2.81 W (PoE)</b> <b>Max.: 4.14 W (12 VDC); 5.14 W (PoE)</b>
<b>Operating Temperature</b>	<b>-10 °C to +45 °C (+14 °F to +113 °F)</b>
<b>Operating Humidity</b>	<b>≤95% (RH), non-condensing</b>
<b>Camera Button</b>	<b>Reset button</b>
<b>Casing Material</b>	<b>Plastic</b>
<b>Product Dimensions</b>	<b>64 mm × 100 mm × 34 mm (2.52" × 3.94" × 1.34") (L × W × H)</b>
<b>Net Weight</b>	<b>0.11 kg (0.24 lb)</b>