DAHUA

DH-C3A

Kod: 00-00005461 · Wifi kamera



DAHUA DH-C3A 2.8mm 3MP CUBE IP Wi-Fi camera, 3MP yüksək görüntü keyfiyyəti, 2.8mm sabit lens və Wi-Fi bağlantısı ilə daxili mühitlər üçün ideal həll təqdim edir. Kompakt kubik dizaynı ilə ev, mağaza və ofis istifadəsi üçün mükəmməl seçimdi.

Texniki göstəricilər

3 MP Meqapixel	**Wifi** Qoşulma
İkitərəfli səs Səs	**10m** Gecə görmə məsafəsi
256Gb Micro SD	**Indoor** İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	1/2.7" CMOS
Max. Resolution	**2304** (H) × **1296** (V)
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Illumination Distance	Up to 10 m (32.81 ft) (IR)
Illuminator On/Off Control	Auto
Illuminator Number	1 (IR LED)
Angle Adjustment	Pan: 0° to 360°; Tilt: -10° to 70°
Lens	
Max. Aperture	F2.0
Field of View	H: 90°; V: 49°; D: 106°
Intelligence	
Human Detection	Yes
Video	
Video Compression	H.265
Video Frame Rate	Main stream: **2304** × **1296**@(1-25/30 fps) sub stream: 640 × 360@(1-25/30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Resolution	3M (**2304** × **1296**); nHD (640 × 360)
Video Bit Rate	H.265: 80 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°

Audio	
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a
Network	
Wi-Fi	IEEE 802.11b/g/n/ax 2.412-2.472 GHz,2.4G
Storage	Micro SD card (up to 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android
Certification	
Certifications	CE
Power	
Power Supply	5 VDC, 1 A
Power Consumption	Basic: 1.65 W; Max.: 2.75 W (H.265+ IR intensity)
Environment	
Operating Temperature	–10 °C to +45 °C (14 °F to +113 °F)
Operating Humidity	≤95%
Structure	
Casing Material	Plastic
Product Dimensions	Φ68 mm × 31.9 mm × 119.2 mm (2.68" × 1.26" × 4.69")
Net Weight	95 g (0.21 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az