

DH-F3D-PV

DAHUA DH-F3D-PV 2.8mm 3MP Fixed-focal Wi-Fi Bullet Network Camera – 3MP çözünlük, sabit fokuslu 2.8mm lens və Wi-Fi dəstəyi ilə bullet tipli IP kameradır. Rəngli gecəgörmə, hərəkət aşkarlama və səsli/işıqlı signal ilə obyektlərinizə ağıllı və dayanıqlı təhlükəsizlik təqdim edir.



Specifications

Model	DH-F3D-PV
Brand	Dahua
Meqapixel	3 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.8" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Min. Illumination	0.005 lux@F1.6 (Color, 30 IRE) 0.0005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)

Illumination Distance	Up to 30 m (98.43 ft) (IR)
	Up to 30 m (98.43 ft) (Warm light)

Illuminator Number	1 (IR LED); 1 (Warm light)
--------------------	----------------------------

Angle Adjustment	Tilt: 0°–90°
	Rotation: 0°–360°

Lens Type	Fixed-focal
-----------	-------------

Focal Length	2.8 mm; 3.6 mm
--------------	----------------

Max. Aperture	F1.6
---------------	------

Field of View	2.8 mm: H: 103°; V: 55°; D: 123°
	3.6 mm: H: 85°; V: 46°; D: 100°

Intelligence

Human Detection	Yes
-----------------	-----

Vehicle Detection	Yes
-------------------	-----

Audio and Video

Video Compression	H.264B; H.264; H.264H; H.265
-------------------	------------------------------

Video Frame Rate	Main stream: 2304 × 1296@(1-25/30 fps)
	sub stream: 640 × 360@(1-25/30 fps)

*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate	H.264: 32 kbps–4096 kbps;
	H.265: 32 kbps–4096 kbps

Day/Night	Auto(ICR)/Color/B/W
-----------	---------------------

WDR	DWDR
-----	------

Motion Detection	OFF/ON (4 areas, rectangular)
------------------	-------------------------------

Image Rotation	0°/180°
----------------	---------

Built-in MIC	Yes, built-in Mic
--------------	-------------------

Built-in Speaker	Yes, built-in speaker
------------------	-----------------------

Audio Compression	G.711a; G.711Mu; PCM
-------------------	----------------------

Network

Network Port	RJ-45 (10/100 Base-T)
--------------	-----------------------

Wi-Fi	IEEE 802.11b/g/n/ax 2.4000–2.4835 GHz, 2.4 G, EIRP≤20 dBm
-------	-----------------------------------------------------------

Wi-Fi Pairing	Bluetooth pairing
---------------	-------------------

Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI
------------------	------------------------------------------------

Storage	Micro SD card (support max. 256 GB)
---------	-------------------------------------

Management	Smart PSS Lite; DSS; DMSS
------------	---------------------------

Software

Mobile Client	Android;iOS
---------------	-------------

General

Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU
Power Supply	12 VDC
Power Consumption	Basic: 2.2 W (12 VDC); Max.: 7.3 W (12 VDC) (H.265 + warm light intensity + sound and light alarm)
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP67
Camera Button	Reset button
Casing Material	Metal + plastic
Product Dimensions	158.3 mm × Φ76.8 mm (6.23" × Φ3.02")
Net Weight	0.34 kg (0.75 lb)