DAHUA

DH-H3D-3F

Kod: 00-00005425 · Wifi kamera



DAHUA DH-H3D-3F 3.6mm 3+3MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera – 3+3MP dual lensli, 3.6mm sabit fokuslu, Wi-Fi bağlantılı daxili Pan & Tilt IP kameradır. Geniş görüntü bucağı, hərəkət aşkarlama, rəngli gecəgörmə və mobil tətbiq dəstəyi ilə ev və ofis üçün ağıllı təhlükəsizlik təmin edir.

Texniki göstəricilər

3 MP Meqapixel	**Wifi** Qoşulma
İkitərəfli səs Səs	**30m** Gecə görmə məsafəsi
256Gb Micro SD	**Indoor** İş mühiti

Ətraflı məlumat

Camera	
Fixed Lens	
Image Sensor	1/3.2'' CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR)
Illuminator Number	2 (IR LED)
Angle Adjustment	0° to 15°
Lens Type	Fixed-focal
Focal Length	3.6 mm
Max. Aperture	F2.0
Field of View	H: 79°; V: 43°; D: 94°
PT Lens	
Image Sensor	1/3.2'' CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	2 (IR LED); 1 (Warm light)
Angle Adjustment	Pan: 0° to 349° Tilt: –5° to 90°
Lens Type	Fixed-focal
Focal Length	3.6 mm
Max. Aperture	F2.0
Field of View	H: 79°; V: 43°; D: 94°
Intelligence	
Human Detection	Yes

Pet Detection	Yes
Audio and Video	
Video Compression	H.265
Video Frame Rate	Main stream: 2304 × 1296@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.265: 512 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax 2.4–2.4835 GHz, 2.4 G, EIRP≤20 dBm & 5.15–5.25 GHz, 5 G, EIRP≤23 dBm@5150–5250 MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android
Function	
Abnormal Sound Alarm	Yes
Privacy Mode	Yes
General	
Certifications	CE

Power Supply	5 VDC
Power Consumption	Basic: 2.3 W Max.: 5.2 W (pulling stream+ IR + PT rotation)
Operating Temperature	–10 °C to +45 °C (–4 °F to +113 °F)
Operating Humidity	≤95% (RH), non-condensing
Casing Material	Plastic
Product Dimensions	Φ80.9 mm × 125.7mm (3.19" × Φ4.95")
Net Weight	233 g (0.51 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az