

## DH-H3D-3F

DAHUA DH-H3D-3F 3.6mm 3+3MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera – 3+3MP dual lensli, 3.6mm sabit fokuslu, Wi-Fi bağlantılı daxili Pan & Tilt IP kameradır. Geniş görüntü bucağı, hərəkət aşkarlama, rəngli gecəgörmə və mobil tətbiq dəstəyi ilə ev və ofis üçün ağıllı təhlükəsizlik təmin edir.



### Specifications

Model	DH-H3D-3F
Brand	Dahua
Meqapixel	3 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Indoor

## KEY FEATURES

## Camera

## Fixed Lens

Image Sensor 1/3.2" CMOS

Max. Resolution 2304 (H) × 1296 (V)

Illumination Distance Up to 30 m (98.43 ft) (IR)

Illuminator Number 2 (IR LED)

Angle Adjustment 0° to 15°

Lens Type Fixed-focal

Focal Length 3.6 mm

Max. Aperture F2.0

Field of View H: 79°; V: 43°; D: 94°

## PT Lens

Image Sensor 1/3.2" CMOS

Max. Resolution 2304 (H) × 1296 (V)

Illumination Distance Up to 30 m (98.43 ft) (IR)  
Up to 30 m (98.43 ft) (Warm light)

Illuminator Number 2 (IR LED); 1 (Warm light)

## Angle Adjustment

Pan: 0° to 349°

Tilt: -5° to 90°

Lens Type Fixed-focal

Focal Length 3.6 mm

Max. Aperture F2.0

Field of View H: 79°; V: 43°; D: 94°

## Intelligence

Human Detection Yes

Pet Detection Yes

## Audio and Video

Video Compression H.265

Video Frame Rate Main stream: 2304 × 1296@15 fps  
sub stream: 640 × 360@15 fps

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.265: 512 kbps–4096 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection Yes

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression G.711a

## Network

Network Port RJ-45 (10/100 Base-T)

---

<b>Wi-Fi</b>	IEEE 802.11a/b/g/n/ac/ax 2.4–2.4835 GHz, 2.4 G, EIRP≤20 dBm & 5.15–5.25 GHz, 5 G, EIRP≤23 dBm@5150–5250 MHz
<b>Wi-Fi Pairing</b>	Bluetooth pairing
<b>Storage</b>	Micro SD card (support max. 256 GB)
<b>Management Software</b>	DMSS
<b>Mobile Client Function</b>	iOS;Android
<b>Abnormal Sound Alarm</b>	Yes
<b>Privacy Mode</b>	Yes
<b>General</b>	
<b>Certifications</b>	CE
<b>Power Supply</b>	5 VDC
<b>Power Consumption</b>	Basic: 2.3 W Max.: 5.2 W (pulling stream+ IR + PT rotation)
<b>Operating Temperature</b>	–10 °C to +45 °C (–4 °F to +113 °F)
<b>Operating Humidity</b>	≤95% (RH), non-condensing
<b>Casing Material</b>	Plastic
<b>Product Dimensions</b>	Φ80.9 mm × 125.7mm (3.19" × Φ4.95")
<b>Net Weight</b>	233 g (0.51 lb)