

DH-H5D-5F

DAHUA DH-H5D-5F Mini PT IP video camera – 5MP əsas + 5MP panoram linzalı, mini ölçülü və Pan & Tilt funksiyalı IP videokameradır. Geniş görüntü sahəsi, ağıllı hərəkət izləmə, dəqiq fokus və yüksək keyfiyyətli görüntü ilə obyektlərinizə tam nəzarət imkanı verir.



Specifications

Model	DH-H5D-5F
Brand	Dahua
Meqapixel	5 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Indoor

KEY FEATURES

Camera

Fixed Lens

Image Sensor 1/3" CMOS

Max. Resolution 2880 (H) × 1620 (V)

Illumination Up to 30 m (98.43 ft) (IR)

Distance

Illuminator Number 2 (IR LED)

Angle Adjustment 0° to 15°

Lens Type Fixed-focal

Focal Length 3.6 mm

Max. Aperture F2.0

Field of View H: 86°; V: 46°; D: 104°

PT Lens

Image Sensor 1/3" CMOS

Max. Resolution 2880 (H) × 1620 (V)

Illumination Up to 30 m (98.43 ft) (IR)

Distance Up to 30 m (98.43 ft) (Warm light)

Illuminator Number 2 (IR LED); 1 (Warm light)

Angle Adjustment

Pan: 0° to 349°

Tilt: -5° to 90°

Lens Type Fixed-focal

Focal Length 3.6 mm

Max. Aperture F2.0

Field of View H: 86°; V: 46°; D: 104°

Intelligence

Human Detection Yes

Pet Detection Yes

Audio and Video

Video Compression H.265

Video Frame Rate Main stream: 2880 × 1620@15 fps

sub stream: 640 × 360@15 fps

*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.265: 768 kbps-4096 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection Yes

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression G.711a

Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax 2.4–2.4835 GHz, 2.4 G, EIRP≤20 dBm & 5.15–5.25 GHz, 5 G, EIRP≤23 dBm@5150–5250 MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client Function	iOS;Android
Abnormal Sound Alarm	Yes
Privacy Mode General	Yes
Certifications	CE
Power Supply	5 VDC
Power Consumption	Basic: 2.5 W; Max.: 5.4 W (pulling stream+ IR + PT rotation)
Operating Temperature	–10 °C to +45 °C (–4 °F to +113 °F)
Operating Humidity	≤95% (RH), non-condensing
Casing Material	Plastic
Product Dimensions	Φ80.9 mm × 125.7mm (3.19" × Φ4.95")
Net Weight	233 g (0.51 lb)