

DH-HAC-HDW1231TP-Z-A

DAHUA DH-HAC-HDW1231TP-Z-A 2MP Starlight HDCVI təhlükəsizlik kamerasıdır. 2.7-12 mm motorizə olunmuş linza, 130 dB güclü WDR və 60 metrə qədər ağıllı İK gecə çəkilişi təklif edir. Daxili mikrofona sahib olan bu metal korpuslu (IP67) model kəsintisiz və keyfiyyətli nəzarət üçün idealdır.



Specifications

Model	DH-HAC-HDW1231TP-Z-A
Brand	Dahua
Növ	Analoq
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.8 - 12mm
???qland?rma	İR
???qland?rma m?saf?si	60 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
?? mühiti	Indoor

KEY FEATURES

Camera

Pixel	2MP
Image Sensor	1/2.8"CMOS
Max. Resolution	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter	PAL: 1/25 s–1/100,000 s
Speed	NTSC: 1/30 s–1/100,000 s
Min. Illumination	0.002lux/F1.5, 30IRE, 0Lux IR on
S/N Ratio	> 65 dB
Illumination Distance	60 m (196.9 ft)
Illuminator On/Off	Auto
Control	
Illuminator Number	2 (IR light)
Pan/Tilt/Rotation	Pan: 0°–360°
Range	Tilt: 0°–78°
	Rotation: 0°–360°

Lens

Lens Type	Motorized vari-focal
Auto Focus	Yes
Lens Mount	φ14
Focal Length	2.7 mm–12 mm
Max. Aperture	F1.5
Field of View	Diagonal: 38°– 123°
	Horizontal: 33°–102°
	Vertical: 19°–53°
Iris Control	Fixed
Close Focus Distance	0.5 m (1.6ft)

Video

Video Frame Rate	CVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; AHD: PAL: 1080P@25fps; NTSC: 1080P@30fps; TVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; CVBS: PAL: 960×576H; NTSC: 960×480H;
Resolution	1080P (1920 × 1080); 960H (960 × 576/960 × 480)
Day/Night	Auto (ICR)
BLC	BLC/WDR/HLC
WDR	130 dB
White Balance	Auto/Area WB
Gain Control	Auto/Manual
Noise Reduction	3D NR
Smart Illumination	Yes
Mirror	Yes
Privacy Masking	Off/On (8 areas,rectangle)
Certifications	
Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input	One channel built-in mic
Power	
Power Supply	12V DC±30%
Power Consumption	Max. 6.4 W (12V DC, IR on)
Environment	
Operating Temperature	−30°C to +60°C (−22°F to +140°F); < 95% (non-condensation)
Storage Temperature	−30°C to +60°C (−22°F to +140°F); < 95% (non-condensation)
Protection	IP67
Structure	
Casing	Metal throughout the whole casing
Camera Dimensions	φ122 mm × 104.8 mm (φ4.80" × 4.13")
Net Weight	0.58 kg (1.3 lb)
Case Weight	0.74 kg (1.6 lb)