

DAHUA

DH-HAC-HDW1231TP-Z-A

Kod: 00-00004842 · Kamera



DAHUA DH-HAC-HDW1231TP-Z-A 2MP Starlight HDCVI təhlükəsizlik kamerasıdır. 2.7-12 mm motorizə olunmuş linza, 130 dB güclü WDR və 60 metrə qədər ağıllı İK gecə çəkilişi təklif edir. Daxili mikrofona sahib olan bu metal korpuslu (IP67) model kəsintisiz və keyfiyyətli nəzarət üçün idealdır.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)

<https://eurotechnology.az/product/dahua/dh-hac-hdw1231tp-z-a>

Texniki göstəricilər



Analoq

Növ



2 MP

Məqapixel



Motorized

Obyektiv



2.8 - 12mm

Fokus



İR

İşıqlandırma



60 m

İşıqlandırma məsafəsi



Mic

Mikrofon



IP67

Qoruma



Metal

Material



Indoor

İş mühiti

Ətraflı məlumat

Camera	
Pixel	2MP
Image Sensor	1/2.8"CMOS
Max. Resolution	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
Min. Illumination	0.002lux/F1.5, 30IRE, 0Lux IR on
S/N Ratio	> 65 dB
Illumination Distance	60 m (196.9 ft)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR light)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°
Lens	
Lens Type	Motorized vari-focal
Auto Focus	Yes
Lens Mount	ø14
Focal Length	2.7 mm–12 mm
Max. Aperture	F1.5
Field of View	Diagonal: 38°– 123° Horizontal: 33°–102° Vertical: 19°–53°
Iris Control	Fixed
Close Focus Distance	0.5 m (1.6ft)
Video	

Video Frame Rate	CVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; AHD: PAL: 1080P@25fps; NTSC: 1080P@30fps; TVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; CVBS: PAL: 960×576H; NTSC: 960×480H;
Resolution	1080P (1920 × 1080); 960H (960 × 576/960 × 480)
Day/Night	Auto (ICR)
BLC	BLC/WDR/HLC
WDR	130 dB
White Balance	Auto/Area WB
Gain Control	Auto/Manual
Noise Reduction	3D NR
Smart Illumination	Yes
Mirror	Yes
Privacy Masking	Off/On (8 areas,rectangle)
Certifications	
Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Port	

Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input	One channel built-in mic
Power	
Power Supply	12V DC±30%
Power Consumption	Max. 6.4 W (12V DC, IR on)
Environment	
Operating Temperature	-30°C to +60°C (-22°F to +140°F); < 95% (non-condensation)
Storage Temperature	-30°C to +60°C (-22°F to +140°F); < 95% (non-condensation)
Protection	IP67
Structure	
Casing	Metal throughout the whole casing
Camera Dimensions	φ122 mm × 104.8 mm (φ4.80" × 4.13")
Net Weight	0.58 kg (1.3 lb)
Gross Weight	0.74 kg (1.6 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az