

HAC-HDW1509TLP- LED

DAHUA DH-HAC-HDW1509TLP- LED (2.7 MM) - 5MP FULL COLOR HDCVI KAMERA



| | |
|-----------------------|---------------------|
| Model | HAC-HDW1509TLP- LED |
| Brend | Dahua |
| Növ | Analoq |
| Meqapixel | 5 MP |
| İşıqlandırma | LED |
| İşıqlandırma məsafəsi | 20 m |
| Obyektiv | Sabit |
| Fokus | 2.8 |
| Qoruma | IP67 |
| Material | Plastik |

Specification

| | |
|-----------------------------------|--|
| Camera | |
| Image Sensor | 1/2.7 inch CMOS |
| Effective Pixels | 2592 (H) × 1944 (V), 5MP |
| Scanning System | Progressive |
| Electronic Shutter Speed | PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s |
| S/N Ratio | >65dB |
| Minimum Illumination | 0.005Lux/F1.2, 0Lux White Light on |
| Fill Light (White Light) Distance | Distance up to 20 m (65.61 ft) |
| Fill Light On/Off Control | Auto; manual |
| Fill Light Number | 1 |
| Pan/Tilt/Rotation Range | Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360° |
| Lens | |
| Lens Type | Fixed-focal |
| Mount Type | M12 |
| Focal Length | 2.8 mm; 3.6 mm |
| Max. Aperture | F1.2 |
| Field of View | 2.8 mm: 129° × 98° × 71° (diagonal × horizontal × vertical) 3.6 mm: 111° × 83° × 56° (diagonal × horizontal × vertical) |
| Iris Type | Fixed iris |
| Close Focus Distance | 2.8 mm: 1.6 m (5.25 ft) 3.6 mm: 2.1 m (6.89 ft) |

| | Lens | Detect | Observe | Recognize | Identify |
|-----------------------|--|-------------------|-------------------|------------------|--------------------|
| DORI Distance | 3.6 mm | 80.0 m (262.5 ft) | 32.0 m (105.0 ft) | 16.0 m (52.5 ft) | 8.0 m (26.2 ft) |
| Video | | | | | |
| Frame Rate | CVI: PAL: 5M@20fps, 4M@25fps, 1080P@25fps; NTSC: 5M@20fps, 4M@30fps, 1080P@30fps AHD: PAL: 5M@20fps, 4M@25fps; NTSC: 5M@20fps, 4M@30fps TVI: PAL: 5M@20fps, 4M@25fps; NTSC: 5M@20fps, 4M@30fps CVBS: PAL: 960H; NTSC: 960H | | | | |
| Resolution | 5M (2592 × 1944); 4M (2560 × 1440); 1080P (1920 × 1080); 960H (704 × 576/704 × 480); | | | | |
| BLC | BLC/HLC/DWDR | | | | |
| WDR | DWDR | | | | |
| White Balance | Auto; manual | | | | |
| Gain Control | Auto; manual | | | | |
| Noise Reduction | 2D NR | | | | |
| Smart Light | Yes | | | | |
| Mirror | Off/On | | | | |
| Privacy Masking | Off/On (8 area, rectangle) | | | | |
| Certifications | | | | | |
| Certifications | CE (EN55032, EN55024, EN50130-4, EN60950-1) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1) | | | | |
| Port | | | | | |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port | | | | |
| Audio Interface | | | | | |
| Audio Input | Built-in mic (-A) | | | | |
| Power | | | | | |
| Power Supply | 12V ±30% DC | | | | |
| Power Consumption | Max 3.0W (12V DC, White Light on) | | | | |
| Environment | | | | | |
| Operating Temperature | -40°C to +60°C (-40°F to 140°F); <95% (non-condensation) | | | | |
| Storage Temperature | -40°C to +60°C (-40°F to 140°F); <95% (non-condensation) | | | | |
| Protection Grade | IP67 | | | | |
| Structure | | | | | |
| Casing | Inner core: metal + plastic Cover: plastic Pedestal: plastic | | | | |
| Camera Dimensions | φ97 mm × 85.8 mm (φ3.82" × 3.38") | | | | |
| Net Weight | 0.22 Kg (0.49 lb) | | | | |
| Gross Weight | 0.28 Kg (0.62 lb) | | | | |