DAHUA

DH-HAC-HFW1231RP-Z-A

Kod: 00-00005322 · Kamera



Dahua DH-HAC-HFW1231RP-Z-A — 2MP Starlight texnologiyalı, rəngli gecə görüntüsü və səsli nəzarət funksiyaları ilə təchiz olunmuş HDCVI kamera. 80 metrə qədər IR işıqlandırma, motorlu varifokal obyektiv və IP67 qoruma səviyyəsi ilə ev və iş yerləri üçün ideal təhlükəsizlik həlli.

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
Motorized Obyektiv	**2.7 - 13.5mm** Fokus
İR İşıqlandırma	**80 m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP67** Qoruma
Metal Material	**Outdoor** İş mühiti

Ətraflı məlumat

Camera	
Pixel	2MP
Image Sensor	1/2.8"CMOS
Max. Resolution	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
Min. Illumination	0.002lux/F1.5, 30IRE, 0Lux IR on
S/N Ratio	> 65 dB
Illumination Distance	80 m (262.5 ft)
Illuminator On/Off Control	Auto
Illuminator Number	4 (IR light)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°
Lens	
Lens Type	Motorized vari-focal
Auto Focus	Yes
Lens Mount	φ14
Focal Length	2.7 mm–12 mm
Max. Aperture	F1.5
Field of View	Diagonal: 38°– 123° Horizontal: 33°–102° Vertical: 19°–53°
Iris Control	Fixed

Close Focus Distance	0.5 m (1.6ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.7 mm	47.6 m (156.2 ft)	19.0 m (62.3 ft)	9.5 m (31.2 ft)	4.76 m (15.6 ft)
	12 mm	132.1 m (433.4 ft)	52.9 m (173.6 ft)	26.4 m (86.6 ft)	13.2 m (43.3 ft)
Video					
Video Frame Rate	CVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; AHD: PAL: 1080P@25fps; NTSC: 1080P@30fps; TVI: PAL: 1080P@25fps; NTSC: 1080P@30fps; CVBS: PAL: 960×576H; NTSC: 960×480H;				
Resolution	1080P (1920 × 1080); 960H (960 × 576/960 × 480)				
Day/Night	Auto (ICR)				
BLC	BLC/WDR/HLC				
WDR	130 dB				
White Balance	Auto/Area WB				
Gain Control	Auto/Manual				
Noise Reduction	3D NR				
Smart Illumination	Yes				

Mirror	Yes
Privacy Masking	Off/On (8 areas, rectangle)
Certifications	
Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input	One channel built-in mic
Power	
Power Supply	12V DC±30%;
Power Consumption	Max. 9.4W (12V DC, IR on)
Environment	
Operating Temperature	–30°C to +60°C (–22°F to +140°F); < 95% (non-condensation)
Storage Temperature	–30°C to +60°C (–22°F to +140°F); < 95% (non-condensation)
Protection	IP67
Structure	
Casing	Metal throughout the whole casing
Camera Dimensions	209.6 mm × 90.4 mm × 90.4 mm (8.30" × 3.56" × 3.56")
Net Weight	0.55 kg (1.2 lb)
Gross Weight	0.76 kg (1.7 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az