eurotech
Taste of technology

**TEXNIKI SƏNƏD**

29.11.2026

**DAHUA**

# DH-HAC-HFW1500TLMP-IL-A-0280B-S2

Kod: 00-00004843 · Kamera




DAHUA HAC-HFW1500TLMP-IL-A-0280B-S2 ( 2.8MM ) 5MP HDCVI KAMERA

## Texniki göstəricilər

| | |
|---|---|
| **Analoq**<br>Növ | **5 MP**<br>Meqapixel |
| **LED**<br>İşıqlandırma | **40 m**<br>İşıqlandırma məsafəsi |
| **Mic**<br>Mikrofon | **Sabit**<br>Obyektiv |
| **2.8mm**<br>Fokus | **IP67**<br>Qoruma |
| **Plastik**<br>Material | **Outdoor**<br>İş mühiti |

## Ətraflı məlumat

| | | | | | |
|---|---|---|---|---|---|
| **Camera** | | | | | |
| Image Sensor | 5 MP CMOS | | | | |
| Max. Resolution | 2880 (H) × 1620 (V) | | | | |
| Scanning System | Progressive | | | | |
| Electronic Shutter Speed | PAL: 1/25 s–1/100000 s<br>NTSC: 1/30 s–1/100000 s | | | | |
| Min. Illumination | 0.05 lux@F1.6 (Color, 30 IRE)<br>0.005 lux@F1.6 (B/W, 30 IRE)<br>0 lux (Illuminator on) | | | | |
| S/N Ratio | >65 dB | | | | |
| Illumination Distance | IR: 40 m (131.23 ft)<br>Warm Light: 40 m (131.23 ft) | | | | |
| Illuminator On/Off Control | Auto/Manual | | | | |
| Illuminator Number | 2 (Warm light);2 (IR light) | | | | |
| Angle Adjustment | Pan: 0°–360°<br>Tilt: 0°–90°<br>Rotation: 0°–360° | | | | |
| **Lens** | | | | | |
| Lens Type | Fixed-focal | | | | |
| Lens Mount | M12 | | | | |
| Focal Length | 2.8 mm; 3.6 mm | | | | |
| Max. Aperture | F1.6 | | | | |
| Field of View | 2.8 mm: H: 106°; V: 56°; D: 125°<br>3.6 mm: H: 92°; V: 48°; D: 109° | | | | |
| Iris Control | Fixed | | | | |
| Close Focus Distance | 2.8 mm: 0.8 m (2.62 ft)<br>3.6 mm: 1.3 m (4.27 ft) | | | | |
| DORI Distance | Lens | Detect | Observe | Recognize | Identify |

| | | | | |
|---|---|---|---|---|
| 2.8 mm | 56 m (183.73 ft) | 22.4 m (73.49 ft) | 11.2 m (36.75 ft) | 5.6 m (18.37 ft) |
| 3.6 mm | 76 m (249.34 ft) | 30.4 m (99.74 ft) | 15.2 m (49.87 ft) | 7.6 m (24.93 ft) |

| | |
|---|---|
| **Video** | |
| Video Frame Rate | CVI:<br>PAL: 5M@25 fps; 4M@25 fps; 1080p@25 fps;<br>NTSC: 5M@25 fps; 4M@30 fps; 1080p@30 fps<br>AHD:<br>PAL: 4M@25 fps;<br>NTSC: 4M@30 fps<br>TVI:<br>PAL: 4M@25 fps;<br>NTSC: 4M@30 fps<br>CVBS:<br>PAL: 960H;<br>NTSC: 960H |
| Resolution | 5M (2880 × 1620); 4M (2560 × 1440); 1080p (1920 × 1080); 960H (960 × 576/960 × 480) |
| Day/Night | Auto(ICR)/Color/B/W |
| BLC | BLC; HLC; DWDR |
| WDR | DWDR |
| White Balance | Auto; Area white balance |
| Gain Control | Auto/Manual |
| Noise Reduction | 2D NR |
| Illumination Mode | Smart IR&WL; WL Mode; IR Mode |
| Mirror | Yes |
| Privacy Masking | Off/On (8 areas, rectangle) |
| **Certification** | |

| | |
|---|---|
| Certifications | CE-LVD: EN 62368-1;<br>CE-EMC: EN 55032; EN 55035;<br>FCC: 47 CFR FCC Part 15, Subpart B;<br>UL: UL62368-1 + CAN/CSA C22.2 No. 62368-1-14 |
| **Port** | |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
| Audio Input | One channel built-in mic |
| **Power** | |
| Power Supply | 12 VDC ± 30% |
| Power Consumption | Max 4.5 W (12 VDC, WLED on) |
| **Environment** | |
| Operating Temperature | –40 °C to +60 °C (–40 °F to +140 °F) |
| Operating Humidity | <95% (RH), non-condensing |
| Storage Temperature | –40 °C to +60 °C (–40 °F to +140 °F) |
| Storage Humidity | <95% (RH), non-condensing |
| Protection | IP67 |
| **Structure** | |
| Casing Material | Metal front cover + plastic rear barrel + metal bracket |
| Product Dimensions | 198.4 mm × 80.2 mm × 76.2 mm (7.81" × 3.16" × 3") |
| Net Weight | 0.3 kg (0.66 lb) |
| Gross Weight | 0.42 kg (0.93 lb) |
| Installation | Wall mount; ceiling mount; vertical pole mount |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az