

IPC-HDW1239T1P-A-LED-S5-QH2-0280B

Dahua DH-IPC-HDW1239T1P-A-LED-S5-QH2-0280B 2 MP IP Full Color (rəngli) səsli kamera;
Piksel 1920×1080; IR işıqlandırma - 15 m; F2.8 mm; Bucaq-107°; Audio (mikrofon)

Model	IPC-HDW1239T1P-A-LED-S5-QH2-0280B
Brend	Dahua
İş mühiti	Indoor
Növ	IP
Meqapixel	2 MP
İşıqlandırma	LED
Mikrofon	Mic
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik



Specification

Technical Specification					
Camera					
Image Sensor	1/2.8" 2Megapixel progressive CMOS				
Effective Pixels	1920(H) x1080(V)				
RAM/ROM	64MB/16MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s				
Minimum Illumination	0.005 lux@F1.6				
S/N Ratio	More than 50dB				
IR Distance	15 m (49.21 ft) (Warm light)				
IR On/Off Control	Auto/ Manual				
IR LEDs	1 (Warm light)				
Lens					
Lens Type	Fixed				
Mount Type	M12				
Focal Length	2.8 mm				
	3.6 mm				
Max. Aperture	F1.6				
Angle of View	H: 107°; V: 56°; D: 127°;H: 88°; V: 44°; D: 105°				
Focus Control	Fixed				
Close Focus Distance	0.7 m (2.30 ft); 1.3 m (4.26 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify

2.8 mm	43.9 m (144.0 ft)	17.5 m (57.4 ft)	8.8 m (28.9 ft)	4.4 m (14.4 ft)
3.6 mm	58.9 m (193.24 ft)	23.6 m (71.9 ft)	11.8 m (36.1 ft)	5.9 m (18.0ft)
PTZ				
Pan/Tilt Range	Pan:0° ~360° ;Tilt:0° ~78° ;Rotation:0° ~360°			
Video				
Compression	H.265; H.264; H.264B; MJPEG (Only supported by the sub stream)			
Streaming Capability	2 Streams			
Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)			
Frame Rate	Main stream: 1920 × 1080@1 fps~25/30 fps			
	Sub stream: 704 × 576@1 fps~25 fps 704 × 480@1 fps~30 fps			
	*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity			
Bit Rate Control	CBR/VBR			
Bit Rate	H.264: 32 kbps~6144 kbps			
	H.265: 12 kbps~6144 kbps			
Day/Night	Color/B/W			
BLC Mode	BLC / HLC /DWDR			

White Balance	Auto/Natural/Street Lamp/Outdoor/Manual/regional custom
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Smart IR	Support
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)
Audio & Alarm	
Built-in MIC	Yes
Audio Compression	G.711A; G.711Mu; G.726
Alarm Event	Network disconnection; IP conflict; illegal access; motion detection; video tampering; audio detection; security exception
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Interoperability	ONVIF (Profile S); CGI; P2P; Genetec
Streaming Method	Unicast / Multicast
Max. User Access	6 (Total bandwidth: 36 M)
Edge Storage	FTP
Web Viewer	IE, Chrome, Firefox

Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Certifications	
Certifications	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Interface	
Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A
Electrical	
Power Supply	DC12V PoE (802.3af)
Power Consumption	Basic power consumption: 1.2 W (12 VDC); 2W (PoE) Max. power consumption (H.265+Warm light intensity): 4.2 W (12V DC); 5.4W (PoE)