

DH-IPC-HDW1339DA-SW-PV

DAHUA DH-IPC-HDW1339DA-SW-PV 2.8mm 3mp Turret Wi-Fi network Camera – 3MP çözünlüklü, 2.8mm lensli turret kamera. Wi-Fi bağlantı, rəngli gecəgörmə, ağıllı hərəkət aşkarlama, işıq və səs siqnalları ilə təhlükəsizliyi maksimum səviyyədə təmin edir. Mobil tətbiq vasitəsilə uzaqdan idarə oluna bilər.



Specifications

Model	DH-IPC-HDW1339DA-SW-PV
Brand	Dahua
Meqapixel	3 MP
Qoʻulma	Wifi
Sʻs	İkitərəfli səs
Gecə görmə mʻsafʻsi	30m
Micro SD	256Gb
ʻʻ mühiti	Indoor

KEY FEATURES

Camera

Image Sensor 1/2.8" CMOS

Max. Resolution 2304 (H) × 1296 (V)

Min. Illumination

0.005 lux@F1.6 (Color, 30 IRE)

0.0005 lux@F1.6 (B/W, 30 IRE)

0 lux (Illuminator on)

Illumination Distance Up to 30 m (98.43 ft) (IR)

Up to 30 m (98.43 ft) (Warm light)

Illuminator Number 1 (IR LED); 1 (Warm light)

Angle Adjustment Pan: 0°–360°

Tilt: 0°–78°

Rotation: 0°–360°

Lens Type Fixed-focal

Focal Length 2.8 mm; 3.6 mm

Max. Aperture F1.6

Field of View 2.8 mm: H: 103°; V: 55°; D: 123°

3.6 mm: H: 85°; V: 46°; D: 100°

Intelligence

Human Detection Yes

Vehicle Detection Yes

Audio and Video

Video Compression H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)

Video Frame Rate Main stream: 2304 × 1296@(1–25/30 fps)

sub stream: 640 × 360@(1–25/30 fps)

*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate

H.264: 32 kbps–6144 kbps

H.265: 32 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression G.711a; G.711Mu; PCM

Network

Network Port RJ-45 (10/100 Base-T)

Wi-Fi IEEE 802.11b/g/n/ax 2.4000–2.4835 GHz, 2.4 G, EIRP≤20 dBm

Interoperability ONVIF (Profile S & Profile G & Profile T); CGI

Wi-Fi Pairing Bluetooth pairing

Storage Micro SD card (support max. 256 GB)

Management Software	Smart PSS Lite; DSS; DMSS
Mobile Client	iOS;Android
General	
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU
Power Supply	12 VDC
Power Consumption	Basic: 2.1 W (12 VDC); Max.: 7.1 W (12 VDC) (H.265 + warm light on+ sound and light alarm)
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP67
Camera Button	Reset button
Casing Material	Metal + plastic
Product Dimensions	102.2 mm × Φ109.9 mm (4.02" × Φ4.33")
Net Weight	0.32 kg (0.71 lb)