

## DH-IPC-HDW1539DA-SW-PV

DAHUA DH-IPC-HDW1539DA-SW-PV 2.8mm 5mp Turret Wi-Fi network Camera – 5MP çözünlüklü, 2.8mm sabit fokuslu lensə malik Wi-Fi turret kameradır. Full rəngli gecəgörmə, ağıllı hərəkət aşkarlama, sirena və işıq signalı, həmçinin mobil tətbiqlə tam uzaqdan nəzarət imkanı təqdim edir.



### Specifications

Model	DH-IPC-HDW1539DA-SW-PV
Brand	Dahua
Meqapixel	5 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Indoor

## KEY FEATURES

## Camera

**Image Sensor** 1/2.7" CMOS**Max. Resolution** 2880 (H) × 1620 (V)**Min. Illumination**

0.007 lux@F1.6 (Color, 30 IRE)

0.0007 lux@F1.6 (B/W, 30 IRE)

0 lux (Illuminator on)

**Illumination** Up to 30 m (98.43 ft) (IR)**Distance** Up to 30 m (98.43 ft) (Warm light)**Illuminator Number** 1 (IR LED); 1 (Warm light)**Angle Adjustment** Pan: 0°–360°

Tilt: 0°–78°

Rotation: 0°–360°

**Lens Type** Fixed-focal**Focal Length** 2.8 mm;3.6 mm**Max. Aperture** F1.6**Field of View** 2.8 mm: H: 108°; V: 57°; D: 129°

3.6 mm: H: 89°; V: 48°; D: 104°

## Intelligence

**Human Detection** Yes**Vehicle Detection** Yes

## Audio and Video

**Video Compression** H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)**Video Frame Rate** Main stream: 2880 × 1620@(1–25/30 fps)

sub stream: 640 × 360@(1–25/30 fps)

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

**Video Bit Rate**

H.264: 32 kbps–6144 kbps

H.265: 32 kbps–6144 kbps

**Day/Night** Auto(ICR)/Color/B/W**WDR** DWDR**Image Rotation** 0°/180°**Built-in MIC** Yes, built-in Mic**Built-in Speaker** Yes, built-in speaker**Audio Compression** G.711a; G.711Mu; PCM

## Network

**Network Port** RJ-45 (10/100 Base-T)**Wi-Fi** IEEE 802.11b/g/n/ax 2.4000–2.4835 GHz, 2.4 G, EIRP≤20 dBm**Wi-Fi Pairing** Bluetooth pairing**Interoperability** ONVIF (Profile S & Profile G & Profile T); CGI**Storage** Micro SD card (support max. 256 GB)

---

<b>Management Software</b>	Smart PSS Lite; DSS; DMSS
<b>Mobile Client</b>	iOS;Android
<b>General</b>	
<b>Certifications</b>	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU
<b>Power Supply</b>	12 VDC
<b>Power Consumption</b>	Basic: 2.1 W (12 VDC);  Max.: 7.1 W (12 VDC) (H.265 + warm light on+ sound and light alarm)
<b>Operating Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Operating Humidity</b>	≤95% (RH), non-condensing
<b>Protection</b>	IP67
<b>Camera Button</b>	Reset button
<b>Casing Material</b>	Metal + plastic
<b>Product Dimensions</b>	102.2 mm × Φ109.9 mm (4.02" × Φ4.33")
<b>Net Weight</b>	0.32 kg (0.71 lb)