DH-IPC-HFW1339DTK1-SW-PV

DAHUA DH-IPC-HFW1339DTK1-SW-PV 2.8mm 2.8mm 3MP Fixed-focal WiFi Bullet Network Camera, 3MP Full-Color texnologiyası ilə yüksək keyfiyyətli görüntülər təqdim edir. 2.8mm sabit obyektiv, Wi-Fi bağlantısı, PIR sensor və aktiv deterrent (səs və işıq siqnalı) xüsusiyyətləri ilə həm gündüz, həm də gecə maksimum təhlükəsizlik təmin edir. Açıq və qapalı məkanlar üçün uyğundur.

Specifications

Model	DH-IPC-HFW1339DTK1-SW-PV
Brand	Dahua
Meqapixel	3 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.8" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Min. Illumination	0.005 lux@F1.6 (Color, 30 IRE)
	0.0005 lux@F1.6 (B/W, 30 IRE)
	0 lux (Illuminator on)
Illumination Distance	Up to 30 m (98.43 ft) (IR)
	Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	1 (Multi-core (IR + warm) light)
Angle Adjustment	Tilt: 0°–90°
	Rotation: 0°–360°
Lens Type	Fixed-focal
Focal Length	2.8 mm; 3.6 mm
Max. Aperture	F1.6
Field of View	2.8 mm: H: 103°; V: 55°; D: 123°
	3.6 mm: H: 85°; V: 46°; D: 100°

Intelligence

Human Detection	Yes
Vehicle Detection	Yes

Audio and Video

Video Compression	H.264B; H.264; H.264H; H.265
Video Frame Rate	Main stream: 2304 × 1296@(1–25/30 fps)
	sub stream: 640 × 360@(1–25/30 fps)
	*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.264: 32 kbps–6144 kbps H.265: 32 kbps–6144 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	OFF/ON (4 areas, rectangular)
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a; G.711Mu; PCM

Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/ax 2.4000–2.4835 GHz, 2.4 G, EIRP≤20 dBm
Wi-Fi Pairing	Bluetooth pairing
Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI
Storage	Micro SD card (support max. 256 GB)
Management Software	Smart PSS Lite; DSS; DMSS
Mobile Client	Android;iOS

General

Certifications	CE
Power Supply	12 VDC
Power Consumption	Basic: 2.2 W (12 VDC); Max.: 6.7 W (12 VDC)
Operating Temperature	−30 °C to +50 °C (−22 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP67
Camera Button	Reset button
Casing Material	Metal + plastic
Product Dimensions	172.4 mm × 83.3 mm × 75.0 mm (6.79" × 3.28" × 2.95") (L × W × H)
Net Weight	0.3 kg (0.66 lb)