

# DH-IPC-HFW3449T1P-AS-PV-0360B

DAHUA DH-IPC-HFW3449T1P-AS-PV 4MP ( 3.6MM ) WIZESENSE NETWORK KAMERA; Audio (səsli)



## Specifications

Model	DH-IPC-HFW3449T1P-AS-PV-0360B
Brand	Dahua
Növ	IP
Meqapixel	4 MP
??qland?rma	LED
Obyektiv	Sabit
Fokus	3.6mm
??qland?rma m?saf?si	30 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.7" CMOS
Max. Resolution	2688 (H) × 1520 (V)
ROM	128 MB
RAM	512 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.003 lux@F1.0 (Color, 30 IRE) 0.0003 lux@F1.0 (B/W, 30 IRE) 0 lux (illuminator on)
S/N Ratio	≥ 56 dB
Illumination	Up to 30 m (98.43 ft) (IR)
Distance	Up to 30 m (98.43 ft) (warm light)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	2 (IR LED) 2 (warm light)
Angle Adjustment	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°

Lens

Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm; 3.6 mm
Field of View	2.8 mm: H: 101°; V: 53°; D: 120° 3.6 mm: H: 82°; V: 44°; D: 96°

Iris Type

Iris Type	Fixed
Close Focus Distance	2.8 mm: 1.5 m (4.92 ft) 3.6 mm: 2.2 m (7.22 ft)

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	66.0 m (216.54 ft)	26.4 m ( 86.61 ft)	13.2 m (43.31 ft)	6.6 m (21.65 ft)
	3.6 mm	78.0 m (255.91 ft)	31.2 m ( 102.36 ft)	15.6 m (51.18 ft)	7.8 m (25.59 ft)

Intelligence

IVS (Perimeter Protection)	Tripwire; intrusion (support the classification and accurate detection of vehicle and human)
SMD 4.0	Less false alarm, longer detection distance
Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos

<b>Quick Pick</b>	With AI NVR, quickly pick up the human/vehicle targets that users are interested in from SMD events
<b>AI SSA</b>	Adopt deep learning algorithms to adjust the parameters of the image to suit the conditions.
<b>Video</b>	
<b>Video Compression</b>	H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)
<b>Smart Codec</b>	Smart H.265+; Smart H.264+
<b>AI Coding</b>	AI H.265; AI H.264
<b>Video Frame Rate</b>	Main stream: 2688 × 1520@(1 fps–30 fps) Sub stream: 704 × 576@(1 fps–25 fps)/704 × 480@(1 fps–30 fps)  Third stream:1920 × 1080@(1 fps–30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity
<b>Stream Capability</b>	3 streams
<b>Resolution</b>	4M (2688 × 1520/2560 × 1440); 3M (2304 × 1296/2048 × 1536); 1080P (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
<b>Bit Rate Control</b>	CBR/VBR
<b>Video Bit Rate</b>	H.264: 32kbps–8192 kbps  H.265: 12kbps–8192 kbps
<b>Day/Night</b>	Auto (ICR)/Color/B/W
<b>BLC</b>	Yes
<b>HLC</b>	Yes
<b>WDR</b>	120 dB
<b>Scene Self-adaptation</b>	Yes
<b>White Balance</b>	Auto; natural; street lamp; outdoor; manual; regional custom
<b>Gain Control</b>	Auto; manual
<b>Noise Reduction</b>	3D NR
<b>Motion Detection</b>	OFF/ON (4 areas)
<b>Region of Interest (RoI)</b>	Yes (4 areas)
<b>Smart Illumination</b>	Yes
<b>Defog</b>	Yes
<b>Image Rotation</b>	0°/90°/180°/270° (Support 90°/270° with 2688 × 1520 resolution and lower)
<b>Mirror</b>	Yes
<b>Privacy Masking</b>	8 areas
<b>Audio</b>	
<b>Built-in Mic</b>	Yes, built-in dual Mic
<b>Built-in speaker</b>	Yes, built-in speaker
<b>Audio Compression</b>	PCM; G.711a; G.711Mu; G.726; G.723
<b>Alarm</b>	
<b>Alarm Event</b>	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; scene changing; audio detection; voltage detection; external alarm; SMD; security exception
<b>Network</b>	
<b>Network</b>	RJ-45 (10/100 Base-T)
<b>SDK and API</b>	Yes
<b>Cyber Security</b>	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade
<b>Protocol</b>	IP;4; IP;6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; CoS; UPnP; NTP;