DAHUA

DH-IPC-PT2249C1-S-PV-PRO

Kod: 00-00006081 · Kamera



Dahua DH-IPC-PT2249C1-S-PV-PRO, WizColor texnologiyalı 2MP PT (fırlanan) IP kameradır. 30 metrə qədər rəngli gecə görüşü, səsli-işıqlı xəbərdarlıq (Active Deterrence) və ikiistiqamətli səs funksiyası ilə ev və obyektlərinizin maksimum təhlükəsizliyini təmin edərək aktiv müdafiə yaradır.

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
LED İşıqlandırma	**30 m** İşıqlandırma məsafəsi
PTZ Obyektiv	**3.6mm** Fokus
Mic Mikrofon	**IP66** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	1/2.8" CMOS
Pixel	2MP
Max. Resolution	1920 (H) × 1080 (V)
ROM	256 MB
RAM	256 MB
Electronic Shutter Speed	1 s–1/100,000 s
Scanning System	Progressive
Min. Illumination	0.0005 lux@F1.0 (Color, 30 IRE); 0 lux (Illuminator on);
Illumination Distance	3.6 mm: 30 m (98.43 ft) (Warm light)
Illuminator On/Off Control	Auto; Manual; Off
Illuminator Number	4 (Warm light)
Lens	
Focal Length	3.6 mm
Max. Aperture	F1.0
Field of View	3.6 mm: H: 89.5°; V: 51°; D: 96°
Close Focus Distance	3.6 mm: 1.7 m (5.58 ft)
PTZ	
Pan/Tilt Range	Pan: 0° to 345°; Tilt: 0° to 90°

Manual Control Speed	Pan: 0.1°–34.5°/s; Tilt: 0.1°–36.4°/s
Preset Speed	Pan: 0.1°–33.8°/s; Tilt: 0.1°–36.3°/s
Preset	80
Tour	8 (up to 6 presets per tour; the stay duration for each preset is 60 to 360 sec and tour interval is 900 to 3,600 sec)
Power-off Memory	Yes
Idle Motion	Preset;Tour
Smart Event	
IVS	Tripwire; Intrusion
Human Detection	Yes
Vehicle Detection	Yes
Intelligence	
Smart Tracking	Auto Tracking Lite
SMD	SMD 3.0
Active Deterrence	
Light Warning	Warm light warning Flash duration: 5 s–30 s; Flash frequency: high, medium, low
Sound Warning	Offers 3 sound alarm. Sound can be set from 0%–100%. Play times can be set from 1-10.
Video	
Video Compression	Smart H.265+;H.265;Smart H.264+;H.264B;H.264M;H.264H;MJPEG(Sub Stream 1)
Streaming Capability	2 streams
Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1(704×576);VGA(640 × 480); CIF(352 × 288)

Video Frame Rate	Main stream: 1920 × 1080@(1–25/30 fps) sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30 fps)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 8 kbps–6,400 kbps H.265: 3 kbps–3,840 kbps
Day/Night	Color/B/W
BLC	Yes
WDR	120 dB
HLC	Yes
White Balance	Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp
Gain Control	Auto; Manual; Gain Priority
Noise Reduction	2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Defog	Electronic
Digital Zoom	16×
Image Rotation	180°
S/N Ratio	≥55 dB
Audio	
Audio Compression	PCM, G.711A, G.711Mu
Built-in MIC	Yes
Built-in Speaker	Yes
Network	
Network Port	RJ-45 (10/100 Base-T)

Network Protocol	HTTP;HTTPS;TCP/IP;IPv4;RTSP;UDP;NTP;DHCP;DNS;DDNS;IPv6;SSL;QoS;FTP;ICMP;IGMP;ARP;RTCP;RTP;RTMP
Interoperability	ONVIF (Profile S & Profile G & Profile T);CGI;SDK
Streaming Method	Unicast/Multicast
User/Host	20 (total bandwidth: 64 M)
Storage	Micro SD card (Up to 512 GB); FTP
Browser	IE: IE 7 and later versions; Chrome; Firefox; Safari
Management Software	DMSS;NVR
Mobile Client	iOS;Android
Function	
Abnormal Sound Alarm	Yes
Certification	
Certifications	CE
Port	
Audio Input	1 channel (built-in mic)
Audio Output	1 channel (built-in speaker)
Alarm Linkage	Capture; recording; audio; light
Alarm Event	Motion/Tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection
Power	
Power Supply	12 VDC, 1A ± 10% PoE (802.3af)
Power Consumption	PoE: Basic: 3.6 W Max: 9.5 W (illuminator + PTZ)
Power Adapter	Optional
Environment	
Operating Temperature	–30 °C to +55 °C (–22 °F to +131 °F)

Operating Humidity	≤95%
Protection	IP66;TVS 2000 V lightning proof; surge protection; voltage transient protection
Structure	
Product Dimensions	153.5 mm × Φ129.3 mm (6.04" × Φ5.09")
Net Weight	0.8kg (1.76 lb)
Gross Weight	1.2kg (2.64 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az