DAHUA

DH-IPC-PTS2249B-E2-S-PV-PRO

Kod: 00-00006082 · Kamera



Dahua DH-IPC-PTS2249B-E2-S-PV-PRO ikili linzalı (2MP+2MP) PT IP kameradır. WizColor texnologiyası ilə gecə rəngli təsvir verir. "Active Deterrence" (siren və işıq) və ikiistiqamətli səs funksiyaları ilə aktiv müdafiə yaradır. Fırlanma (PT) və sabit baxış bucağını bir cihazda birləşdirir.

Texniki göstəricilər

IP	**2 MP**
Növ	Meqapixel
LED	**30 m**
İşıqlandırma	İşıqlandırma məsafəsi
Mic	**PTZ**
Mikrofon	Obyektiv
3.6mm	**IP66**
Fokus	Qoruma
Plastik	**Outdoor**
Material	İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	Channel 1 (PT Lens): 1/2.9" CMOS Channel 2 (Fixed Lens): 1/2.9" CMOS
Max. Resolution	Channel 1 (PT Lens): 1920 (H) × 1080 (V) Channel 2 (Fixed Lens): 1920 (H) × 1080 (V)
ROM	128 MB
RAM	256 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.0006 lux@F1.0
S/N Ratio	>56 dB
Illumination Distance	Up to 30 m (98.43 ft) (Warm light)
Illuminator On/Off Control	Auto; Manual
Illuminator Number	4 (Warm light)
Lens	
Lens Type	Channel 1 (PT Lens): Fixed-focal Channel 2 (Fixed Lens): Fixed-focal
Lens Mount	M12
Focal Length	Channel 1 (PT Lens): 3.6 mm Channel 2 (Fixed Lens): 3.6 mm
Max. Aperture	Channel 1 (PT Lens): F1.0 Channel 2 (Fixed Lens): F1.0
Field of View	Channel 1 (PT Lens): H: 81°; V: 44°; D: 95° Channel 2 (Fixed Lens): H: 81°; V: 44°; D: 95°
Iris Control	Fixed
Close Focus Distance	Channel 1 (PT Lens): 1.7 m (5.58 ft) Channel 2 (Fixed Lens): 1.7 m (5.58 ft)

Intelligence	
IVS (Perimeter Protection)	Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
SMD	SMD Plus
Smart Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
Video	
Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)
Smart Codec	Smart H.265+; Smart H.264+
Video Frame Rate	Channel 1 (PT Lens): Main stream: 1920 × 1080@(1–25/30 fps) sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30 fps) Channel 2 (Fixed Lens): Main stream: 1920 × 1080@(1–25/30 fps) sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Streaming Capability	2 streams
Resolution	Channel 1 (PT Lens): 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240) Channel 2 (Fixed Lens): 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	VBR; CBR
Video Bit Rate	H.264: 32 kbps–4096 kbps; H.265: 12 kbps–4096 kbps
Day/Night	Color/B/W
BLC	Yes
HLC	Yes
WDR	120 dB
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Gain Control	Auto/Manual

Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest (RoI)	Yes (4 areas)
Smart Illumination	Yes
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower)
Mirror	Yes
Privacy Masking	4 areas
LDC	Yes
Audio	
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a; G.711Mu; PCM; G.726
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; audio detection; voltage detection; SMD; security exception
Network	
Network Port	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; P2P; Bonjour; Auto Registration
Security	Digest; WSSE; Account lockout; Security logs; IP/MAC filtering; Generation and importing of X.509 certification; syslog; HTTPS; 802.1x; Trusted boot; Trusted execution; Trusted upgrade; Session security; Security warning
Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI
User/Host	20 (Total bandwidth: 48 M)
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS

Browser	IE; Chrome; Firefox
Management Software	Smart PSS Lite; DSS; DMSS
Mobile Client	Android;iOS
Function	
Light Warning	Warm light warning Flash/Solid on duration: 5 s–30 s Flash frequency: high, medium, low
Sound Warning	Offers 3 sound alarms and supports importing custom sound alarms. Sound: 0–100. Play times can be set from 1 to 10.
PTZ	
Pan/Tilt Range	Channel 1 (PT Lens): Pan: 0° to 350°; Tilt: 0° to 90°; Channel 2 (Fixed Lens): Pan: 0° to 326°; Tilt: –10° to 15°
Manual Control Speed	Pan: 0.1°/s–55.4°/s; Tilt: 0.1°/s–29.3°/s
Preset	300
Preset Speed	Pan: 55.4°/s; Tilt: 29.3°/s
Tour	8 (up to 32 presets per tour)
Power-off Memory	Yes
Idle Motion	Tour;Preset
Certification	
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU
Power	
Power Supply	12 VDC (±30%); PoE (802.3af)
Power Consumption	Basic: 2.3 W (12 VDC); 3.1 W (PoE); Max.: 9.2 W (12 VDC); 10.5 W (PoE) (intelligence on + WDR + illuminator on + PT rotation + speaker on)
Environment	

Operating Temperature	–40 °C to +50 °C (–40 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing
Storage Temperature	–40 °C to +50 °C (–40 °F to +122 °F)
Storage Humidity	≤95% (RH), non-condensing
Protection	IP66
Structure	
Casing Material	Plastic
Product Dimensions	110.1 mm × 159.4 mm × 210 mm (4.33" × 6.28" × 8.27") (L × W × H)
Net Weight	0.62 kg (1.37 lb)
Gross Weight	0.87 kg (1.92 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az