DAHUA

DH-P3AS-PV

Kod: 00-00005430 · Wifi kamera



DAHUA DH-P3AS-PV 3MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera – 3MP çözünürlüklü, 3.6mm sabit fokuslu obyektivə malik, Wi-Fi bağlantılı xarici IP kameradır. Pan & Tilt funksiyası, IR gecəgörmə, hərəkət aşkarlama və mobil tətbiq ilə uzaqdan tam nəzarət imkanı təqdim edir.

Texniki göstəricilər

3 MP Meqapixel	**Wifi** Qoşulma
İkitərəfli səs Səs	**30m** Gecə görmə məsafəsi
256Gb Micro SD	**Outdoor** İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	2 (Multi-core (IR + warm) light)
Angle Adjustment	Pan: 0° to 345° Tilt: 0° to 90° Rotation: 0° to 345°
Lens Type	Fixed-focal
Focal Length	4.0 mm
Max. Aperture	F2.0
Field of View	H: 83°; V: 45°; D: 98°
Intelligence	
Human Detection	Yes
Vehicle Detection	Yes
Audio and Video	
Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)
Video Frame Rate	Main stream: 2304 × 1296@(1–25/30 fps) sub stream: 640 × 360@(1–25/30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.264: 32 kbps–6144 kbps; H.265: 32 kbps–6144 kbps
Day/Night	Auto(ICR)/Color/B/W

WDR	DWDR
Motion Detection	OFF/ON (4 areas, rectangular)
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a; G.711Mu; PCM
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax 2.4 G & 5 G, EIRP≤20 dBm@2400–2483.5 MHz (CE), EIRP≤23 dBm@5150–5250 MHz (CE), EIRP≤20 dBm@5250–5350 MHz (CE), EIRP≤20 dBm@5470–5725 MHz (CE), EIRP≤14 dBm@5725–5875 MHz (CE)
Wi-Fi Pairing	Bluetooth pairing
Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI
Storage	Micro SD card (support max. 256 GB)
Management Software	Smart PSS Lite; DSS; DMSS
Mobile Client	Android;iOS
Function	
Abnormal Sound Alarm	Yes
General	
Certifications	CE
Power Supply	12 VDC (±30%)
Power Consumption	Basic: 1.8 W (12 VDC) Max.: 13.8 W (12 VDC) (illuminator intensity + red and blue active deterrence + speaker on + PT rotation + Wi-Fi pulling stream + WDR)
Operating Temperature	–30 °C to +55 °C (–22 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing

Protection	IP66
Camera Button	Reset button
Casing Material	Plastic
Product Dimensions	125.4 mm × 110 mm × 140.3 mm (4.94" × 4.37" × 5.52") (L × W × H)
Net Weight	0.4 kg (0.88 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az