

## DH-P3AS-PV

DAHUA DH-P3AS-PV 3MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera – 3MP çözünlüklü, 3.6mm sabit fokuslu obyektivə malik, Wi-Fi bağlantılı xarici IP kameradır. Pan & Tilt funksiyası, IR gecəgörmə, hərəkət aşkarlama və mobil tətbiq ilə uzaqdan tam nəzarət imkanı təqdim edir.



### Specifications

|                     |                |
|---------------------|----------------|
| Model               | DH-P3AS-PV     |
| Brand               | Dahua          |
| Meqapixel           | 3 MP           |
| Qo?ulma             | Wifi           |
| S?s                 | İkitərəfli səs |
| Gec? görm? m?saf?si | 30m            |
| Micro SD            | 256Gb          |
| ?? mühiti           | Outdoor        |

## KEY FEATURES

## Camera

Image Sensor 1/2.8" CMOS

Max. Resolution 2304 (H) × 1296 (V)

## Min. Illumination

0.01 lux@F2.0 (Color, 30 IRE)

0.001 lux@F2.0 (B/W, 30 IRE)

0 lux (Illuminator on)

Illumination Distance Up to 30 m (98.43 ft) (IR)

Up to 30 m (98.43 ft) (Warm light)

Illuminator Number 2 (Multi-core (IR + warm) light)

Angle Adjustment Pan: 0° to 345°

Tilt: 0° to 90°

Rotation: 0° to 345°

Lens Type Fixed-focal

Focal Length 4.0 mm

Max. Aperture F2.0

Field of View H: 83°; V: 45°; D: 98°

## Intelligence

Human Detection Yes

Vehicle Detection Yes

## Audio and Video

Video Compression H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)

Video Frame Rate Main stream: 2304 × 1296@(1–25/30 fps)

sub stream: 640 × 360@(1–25/30 fps)

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.264: 32 kbps–6144 kbps;

H.265: 32 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection OFF/ON (4 areas, rectangular)

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression G.711a; G.711Mu; PCM

## Network

Network Port RJ-45 (10/100 Base-T)

## Wi-Fi

IEEE 802.11a/b/g/n/ac/ax 2.4 G &amp; 5 G, EIRP≤20 dBm@2400–2483.5 MHz (CE), EIRP≤23 dBm@5150–5250 MHz (CE),

EIRP≤20 dBm@5250–5350 MHz (CE), EIRP≤20 dBm@5470–5725 MHz (CE), EIRP≤14 dBm@5725–5875 MHz (CE)

Wi-Fi Pairing Bluetooth pairing

Interoperability ONVIF (Profile S &amp; Profile G &amp; Profile T); CGI

---

|                              |   |
|------------------------------|---|
| <b>Storage</b>               | Micro SD card (support max. 256 GB)   |
| <b>Management</b>            | Smart PSS Lite; DSS; DMSS   |
| <b>Software</b>              |   |
| <b>Mobile Client</b>         | Android;iOS   |
| <b>Function</b>              |   |
| <b>Abnormal Sound Alarm</b>  | Yes   |
| <b>General</b>               |   |
| <b>Certifications</b>        | CE  |
| <b>Power Supply</b>          | 12 VDC (±30%)   |
| <b>Power Consumption</b>     | Basic: 1.8 W (12 VDC)<br>Max.: 13.8 W (12 VDC) (illuminator intensity + red and blue active deterrence + speaker on + PT rotation + Wi-Fi pulling stream + WDR) |
| <b>Operating Temperature</b> | -30 °C to +55 °C (-22 °F to +122 °F)  |
| <b>Operating Humidity</b>    | ≤95% (RH), non-condensing   |
| <b>Protection</b>            | IP66  |
| <b>Camera Button</b>         | Reset button  |
| <b>Casing Material</b>       | Plastic   |
| <b>Product Dimensions</b>    | 125.4 mm × 110 mm × 140.3 mm (4.94" × 4.37" × 5.52") (L × W × H)  |
| <b>Net Weight</b>            | 0.4 kg (0.88 lb)  |